



INVEST IN THE FUTURE

CHARGE



CHARGERS - BATTERY SUPPORT UNITS - BOOSTERS - STARTERS
TESTERS - PORTABLE ENERGY - JUMPER CABLES - EV CHARGING - ACCESSORIES

2026

A solid
manufacturing
group

900 people

C1+
Credit Rating
Banque de France

€ 140 000 000

55 000 m²
2 factories



FRENCH MANUFACTURER
SINCE 1964

A family
company



Nicolas & Bruno
Bouygues



Global coverage
125 countries

4 catalogues
3 500+ references



MMA/SAW
TIG/GTAW
MIG-MAG/GMAW-FCAW
Plasma cutting
Induction heating
Stud welding
Spot welding
Accessories
Protection
Consumables



Spot welding
Dent pulling
MIG-MAG/GMAW-FCAW
Plasma cutting
Induction heating
Riveting
Lifting
Bodyshop tools



Chargers
Battery support units
Boosters
Starters
Testers
Portable energy
Jumper cables
EV charging
Accessories



Releasing
Shrink-fitting
Stripping
Straightening
Dent removal
Bending
Brazing



GYS FRANCE - HEADQUARTERS
Laval

**GYS LOGISTICS
CENTER**
Laval



GYS GERMANY
Aachen



GYS U.K.
Rugby



GYS CHINA
Shanghai



GYS ITALIA
Venezia



GYS IBERICA
Madrid

Table of contents

CHARGERS & BATTERY SUPPORT UNIT	6 > 47
CHARGERS & STARTERS	48 > 51
BOOSTERS	52 > 71
ACCESSORIES	72 > 91



★★★★★ **THEY TRUST US** ★★★★★

ILS NOUS FONT CONFIANCE



LAND ROVER

JAGUAR

MERCEDES

smart



VOLKSWAGEN GROUP



TESLA
APPROVED
COLLISION TOOLS, EQUIPMENT & CONSUMABLES



Jeep



EICHER



Li Auto



BMW

MINI

ROLLS ROYCE



DAF



INVEST IN THE FUTURE



CHARGERS & BATTERY SUPPORT UNITS

6 - 12 - 16 - 24 - 36 - 48 V

CHARGERS - GYSFLASH

GYSFLASH Pb	6
GYSFLASH LITHIUM	9
GYSFLASH Pb / LITHIUM	10
GYSFLASH ON BOARD	18

CONVERTER DC/DC

ENERGYS DC · DC CHARGER	19
-------------------------	----

BATTERY SUPPORT UNITS

GYSFLASH PRO	20
GYSFLASH PRO CNT	22
STARTFLASH	28
BATTERY BALANCING	30
CONNECTED TECHNOLOGY & ACCESSORIES	34

MORE CHARGERS

ARTIC	40
ENERGY / TCB	41
CT / CA / WATTMATIC	42
BATIUM	44
DIAG-BATIUM	46
MULTICHARGE STATION	47

GYSFLASH TECHNOLOGY

SSM

Save and load settings. Automatic restart in case of power cut.
Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.
Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.

START STOP

Start/stop Engine :
Compatible with Start/Stop vehicles.
Compatible véhicules Start/Stop.
Geeignet für START-STOP- Fahrzeuge.

CAN BUS

Can Bus ready: compatible with Can Bus Technology, the Gysflash can be connected to the motorcycle 12V socket (cable is optional).
Can bus ready : compatible avec la technologie Can Bus, le Gysflash se branche directement sur la prise 12 V de la moto (câble en option).
Can-Bus Ready: Mit der Can-Bus Technologie kompatibel. Das GYSFLASH wird direkt an den 12V-Anschluss des Motorrads angeschlossen (Kabel optional).

Recovery

Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.
Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.
Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).

Cold

“Cold charge” mode: performance-enhancing charging mode for cold or freezing weather conditions.
Mode “Cold charge”: optimisation des performances en cas de temps froid ou de gel.
-Cold Charge--Modus: Leistungsoptimierung bei kaltem Wetter oder bei Frost.

Temp

Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.
Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.
Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

Power

Power supply mode: Optimum floating charge, ideal for use during battery change to protect vehicle memory.
Also for when the vehicle is not in use for extended periods or for demonstration use.
Source d'énergie : mode de maintien optimal de l'état de charge. Idéal pour les véhicules en hivernage, de démonstration, ou pour le remplacement de batterie.
Energiequelle: Aufrechterhaltung des Batteriezustands. Ideal für Saison-, Ausstellungsfahrzeuge oder bei Batteriewechsel.

SMART CHARGE

7 STEP

8 STEP

1. Status analysis

2. Recovery

3. Test desulphation

4. Desulphation

5. Fast charge 80%

6. Absorption

7. Refresh (for "8 step" only)

8. Floating 100%

U

1

2

3

4

5

6

7

8

I

REFRESH

8 STEP

Rebalancing the battery cells for greater (not available on all models).
Rééquilibrage des cellules de la batterie pour plus de longévité (suivant modèle).
Regenerierung der Batteriezellen für eine längere Lebensdauer (je nach Modell).

110V

✓

✓

✓

GYSFLASH 4.12 S

GYSFLASH 1.12 PL S

4.12

1.12 PL

GYSFLASH Pb

CHARGERS

Pb

1.12

4.12

4.12S

BEST
SELLER

DESIGN
GYS
FRANCE

MADE IN
GYS CHINA

YouTube

PLAYLIST
GYSFLASH

IP 65

INGRESS PROTECTION

GYSFLASH
1.12, 4.12, 6.12, 8.12, 12.12,
6 HERITAGE, 6.24, 9.24, 1.12 PL,
8.12 PL, 6.24 PL, 3.48 PL,
1.12 Lithium, 6.12 Lithium

GYSFLASH 1.12

1 A

GO > 7 V

SSM

START STOP

CAN BUS

Recovery

7 STEP

F FLASH Connector

1.45 m

0.45 m

0.45 m

029361

029514

GYSFLASH 4.12 & 4.12S

0.8/4 A

GO > 2 V

SSM

START STOP

CAN BUS

Recovery

7 STEP

F FLASH Connector

1.45 m

0.45 m

0.45 m

4.12

029422

029521

4.12S (110 V)

069190

072701

072817

GYSFLASH 6.12

0.8/6 A

GO > 2 V

SSM

START STOP

CAN BUS

Recovery

7 STEP

F FLASH Connector

1.45 m

0.45 m

0.45 m

029378

029613

GYSFLASH 8.12

8 A

GO > 2 V

SSM

START STOP

Recovery

8 STEP

1.9 m

029385

029545

GYSFLASH 12.12

12 A

GO > 2 V

SSM

START STOP

Recovery

8 STEP

S SAE Connector

0.40 m

1.45 m

029392

029552

	50 / 60 Hz		Power	I _{charge}		Charge	Maintenance		Ondulation/ Ripple	Charging curve		IP				L×W×H cm / kg
GYSFLASH 1.12	220-240 V AC	1 m	18 W	1 A	12 V	2 × 32 Ah	2 × 100 Ah	<0.4 Ah/month	<150 mV Rms	I _{UoU}	7 steps	IP 65	0.44 kg	13 × 8 × 3.8 cm	30 × 15.5 × 6 / 0.6	
GYSFLASH 4.12 GYSFLASH 4.12S	220-240 V AC 100-127 V AC	2 m	70 W	0.8/4 A	12 V	1.2 × 90 Ah	1.2 × 130 Ah	<0.4 Ah/month	<150 mV Rms	I _{UoU}	7 steps	IP 65	0.69 kg	17 × 9 × 5.1 cm	34.5 × 17.9 × 36.2 / 0.89	
GYSFLASH 6.12	220-240 V AC	2 m	90 W	0.8/6 A	12 V	1.2 × 125 Ah	1.2 × 170 Ah	<0.4 Ah/month	<150 mV Rms	I _{UoU}	8 steps	IP 65	0.77 kg	19 × 10 × 5.2 cm	36 × 19.5 × 7 / 1	
GYSFLASH 8.12	220-240 V AC	2 m	130 W	8 A	12 V	15 × 160 Ah	15 × 240 Ah	<0.4 Ah/month	<150 mV Rms	I _{UoU}	8 steps	IP 65	0.85 kg	19 × 10 × 5.2 cm	36 × 19.5 × 7 / 1	
GYSFLASH 12.12	220-240 V AC	2 m	195 W	12 A	12 V	20 × 250 Ah	20 × 330 Ah	<0.4 Ah/month	<100 mV Rms	I _{UoU}	8 steps	IP 65	1.1 kg	22.1 × 11.1 × 5.8 cm	36.4 × 20 × 6.8 / 1.3	



GYSFLASH Pb


CHARGERS Pb



HERITAGE • 6/12V

GYSFLASH 6 HERITAGE

0.8/6 A



029538

DESIGN
GYS
FRANCE

MADE IN
GYS CHINA


8

 PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN	 50 / 60 Hz	 Power	 I _{charge}	 V	 Charge	 Maintenance	 Z _z	Ondulation / Ripple	Charging curve		IP				
	L × W × H cm / kg														
GYSFLASH 6 HERITAGE	220-240 V AC	2 m	90 W	0,8/6 A	6/12 V	1.2 › 125 Ah	1.2 › 170 Ah	<0.4 Ah /month	<150 mV Rms	IUoU	8 steps	IP 65	0.77 kg	19 × 10 × 5.2 cm	36.5 × 19.4 × 7 cm / 1
GYSFLASH 6.24	220-240 V AC	2 m	130 W	0,8/6 A	6/12 V	1.2 › 125 Ah	1.2 › 170 Ah	<0.4 Ah /month	<150 mV Rms	IUoU	7 step	IP 65	0.85 kg	19 × 10 × 5.2 cm	36.5 × 19.5 × 7 cm / 1
				0,8/4 A	24 V	1.2 › 100 Ah	1.2 › 140 Ah								
GYSFLASH 9.24	220-240 V AC	2 m	190 W	9 A	6/12 V	18 › 220 Ah	18 › 300 Ah	<0.4 Ah /month	<100 mV Rms	IUoU	8 step	IP 65	1.1 kg	22.1 × 11.1 × 5.8 cm	36.5 × 19.5 × 7 cm / 1.3
				6 A	24 V	15 › 125 Ah	15 › 170 Ah								



GYSFLASH 6.24

0.8/6 A



029460

029644

GYSFLASH 9.24

9 A



029477

029651

YouTube



PLAYLIST
GYSFLASH

GYSFLASH TECHNOLOGY



Save and load settings. Automatic restart in case of power cut.

Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.

Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.



Start/stop Engine :

Compatible with Start/Stop vehicles.

Compatible véhicules Start/Stop.

Geeignet für START-STOP- Fahrzeuge.



Can Bus ready: compatible with Can Bus Technology, the Gysflash can be connected to the motorcycle 12V socket (cable is optional).

Can bus ready : compatible avec la technologie Can Bus, le Gysflash se branche directement sur la prise 12 V de la moto (câble en option).

Can-Bus Ready: Mit der Can-Bus Technologie kompatibel. Das GYSFLASH wird direkt an den 12V-Anschluss des Motorrads angeschlossen (Kabel optional).



Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.

Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.

Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).



Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.


Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.

Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

SMART CHARGE 7 STEP / 8 STEP / 8 STEP LiFePO₄

Pb

1. Status analysis
2. Recovery
3. Test desulphation
4. Desulphation
5. Fast charge 80%
6. Absorption
7. Refresh (for "8 step" only)
8. Floating 100%




Rebalancing of the battery cells for greater longevity (not available on all models).

Rééquilibrage des cellules de la batterie pour plus de longévité (suivant modèle).

Regenerierung der Batteriezellen für eine längere Lebensdauer (je nach Modell).

LiFePO₄ (LFP)

1. UVP Wake up - Status analysis
2. Recovery
3. Fast charge 90%
4. Absorption 95%
5. Test
6. Completion
7. Equalization
8. Floating 100%



UVP Wake up (Under Voltage Protection)

Battery reactivation when in UVP protection.

Réactivation de la batterie en protection UVP.

Reaktivierung der Batterie mit UVP-Schutz.

Equalizing Balancing System

Balancing of the battery cells.

Équilibrage des cellules.

Ausgleich der Batteriezellen.



GYSFLASH LITHIUM

CHARGERS LiFePO₄



12V

GYSFLASH 1.12 Lithium


1 A



029675

GYSFLASH 6.12 Lithium

4/6 A



029729

DESIGN
GYS FRANCE
MADE IN
GYS CHINA

DESIGN GYS FRANCE MADE IN GYS CHINA	 50 / 60 Hz	 Power	 I charge	 V	 Charge	 Maintenance	 Zz	Ondulation / Ripple	Charging curve	 IP			 L × W × H cm / kg		
GYSFLASH 1.12 Lithium	220-240 V AC	1 m	18 W	1 A	12 V	0.5 › 20 Ah	0.5 › 50 Ah	<0.4 Ah/ month	<150 mV Rms	IUoU	8 step	IP 65	0.44 kg	13 × 8 × 3.8 cm	29.7 × 15 × 5.7 / 0.6
GYSFLASH 6.12 Lithium	220-240 V AC	2 m	90 W	4/6 A	12 V	1.2 › 125 Ah	1.2 › 170 Ah	<0.4 Ah/ month	<150 mV Rms	IUoU	8 step	IP 65	0.77 kg	19 × 10 × 5.2 cm	36.5 × 19.5 × 7 / 1



9

GYSFLASH LITHIUM

CHARGERS



CHARGERS


Pb / LiFePO₄



12V

GYSFLASH 1.12 PL & 1.12 PL S

1 A



1.12 PL
026902

1.12 PL S (110 V)
070851
072794
072824

GYSFLASH 8.12 PL

1/4 / 8 A



069282

GYSFLASH 18.12 PL

7/12 / 18 A

GO > 2 V




026926

OPTION

Gysflash 18.12 PL,
30.12 PL, 20.12/24 PL,
10.36/48 PL

Magnetfix 20
026063



x4



12/24V

GYSFLASH 30.12 PL

7/15 / 30 A



029668
026070

GYSFLASH 20.12/24 PL

7/15 / 20 A



026049
027558

 PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN		 50 / 60 Hz		Power	I _{charge}	 V	 Charge	 Maintenance	 Z _z	Ondulation/ Ripple	 Charging curve	 IP			L × W × H cm / kg	
DESIGN GYS FRANCE	GYSFLASH 1.12 PL	220-240 V AC	2 m	20 W	1 A	12 V	2 × 32 Ah (Pb) 0.5 × 20 Ah (LiFePO4)	2 × 100 Ah (Pb) 0.5 × 50 Ah (LiFePO4)	<0.4 Ah/ month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 65	0,69 kg	17 × 9 × 5.1 cm	33 × 17.5 × 6 / 0.8
	GYSFLASH 1.12 PL S	100-127 V AC														
MADE IN GYS CHINA	GYSFLASH 8.12 PL	220-240 V AC	2 m	130 W	1/4/8 A	12 V	2 × 160Ah (Pb) 1.2 × 160 Ah (LiFePO4)	2 × 240Ah (Pb) 1.2 × 240 Ah (LiFePO4)	<0.4 Ah/ month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 65	0,85 kg	19 × 10 × 5.2 cm	—
MADE IN FRANCE	GYSFLASH 18.12 PL	220-240 V AC	2 m	300 W	7/12/18 A	12 V	15 × 270 Ah (Pb) 7 × 270 Ah (LiFePO4)		<0.5 Ah/ month	<100 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 31	1,55 kg	19 × 19 × 7.3 cm	30 × 22 × 9 / 1.9

 PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN				Power	I _{charge}	 V	 Charge	 Maintenance	 Z _z	Ondulation/ Ripple	Charging curve		IP			
		50 / 60 Hz														L × W × H cm / kg
MADE IN FRANCE	GYSFLASH 30.12 PL	220-240 V AC	2 m	500 W	7/15/30 A	12 V	15 > 375 Ah (Pb) 7 > 375 Ah (LiFePO4)		<0.5 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 31	1,85 kg	19 × 19 × 7.3 cm	30 × 22 × 9 / 2.2
	GYSFLASH 20.12/24 PL	220-240 V AC	2 m	500 W	7/15/20 A 7/15 A	12 V 24 V	15 > 300 Ah (Pb) 7 > 300 Ah (LiFePO4) 15 > 240 Ah (Pb) 7 > 240 Ah (LiFePO4)		<1 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 31	1,85 kg	19 × 19 × 7.3 cm	30 × 22 × 8.5 / 2.2

GYSFLASH TECHNOLOGY

SSM

Save and load settings. Automatic restart in case of power cut.
Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.
Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.

START STOP

Start/stop Engine :
Compatible with Start/Stop vehicles.
Compatible véhicules Start/Stop.
Geeignet für START-STOP- Fahrzeuge.

Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.
Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.
Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).

t°

Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.
Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.
Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

SMART CHARGE

7 STEP / 8 STEP

Pb

1. Status analysis

2. Recovery

3. Test desulphation

4. Desulphation

5. Fast charge 80%

6. Absorption

7. Floating 100%

LiFePO4 (LFP) / Li-ion

1. UVP Wake up

2. Status analysis

3. Recovery

4. Fast charge 90%

5. Test

6. Completion

7. Equalization

8. Floating 100%

UVP Wake up (Under Voltage Protection)

Battery reactivation when in UVP protection.
Réactivation de la batterie en protection UVP.
Reaktivierung der Batterie mit UVP-Schutz.

Equalizing Balancing System

Balancing of the battery cells.
Équilibrage des cellules.
Ausgleich der Batteriezellen.

GYSFLASH Pb / LITHIUM

CHARGER
Pb / LiFePO₄

INTENSIVE

SC SMART COOLING TECHNOLOGY

100% DUST PROOF

SILENT

IP 23
INDOOR / OUTDOOR

12V

GYSFLASH 32.12 PL

7/15 / 30 A

GO > 2 V

SSM

START STOP

7 STEP Pb

8 STEP LiFePO₄

2,5 m - 6 mm²

027381

PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN	50 / 60 Hz		Power	I _{charge}	V	Charge	Maintenance		Ondulation/ Ripple	Charging curve	IP			L × W × H cm / kg
MADE IN FRANCE	GYSFLASH 32.12 PL	230V	2.5 m	500W	7/15/30 A	12 V	10 × 400 Ah	<0.5 Ah/month	<150 mV Rms	IUoU	IP 23	4,7 kg	8 × 25 × 20 cm	36 × 27,5 × 20,5 / 4,6
	GYSFLASH 15.24 XTREM	230V	2.5 m	500W	7/10/15 A	12/24V	5 × 240 Ah	<1 Ah/month	<150 mV Rms	IUoU	IP 65	5,4 kg	7,5 × 25 × 21 cm	27 × 20 × 36 / 5,4

GYSFLASH Pb

CHARGER
Pb

INTENSIVE

SHOCK RESISTANT

12 / 24V

GYSFLASH 15.24 XTREM

15 A

GO > 2 V

SSM

START STOP

7 STEP Pb

SC

5 m - 4 mm²

025813

ROBUST & SAFE

2 pts connection

Double insulation

included for Gysflash 15.24 XTREM 028760

INCLUDED

Fixing kit
for Gysflash 32.12 PL,
15.24 XTREM

OPTIONS

NATO CONNECTOR 026780

2 pts/NATO Spiral 5 m 028968

2 pts/NATO 5 m - 4 mm² 025837

2 pts/DIN 1490 Emergency vehicle 5 m 028777



GYSFLASH TECHNOLOGY



Save and load settings. Automatic restart in case of power cut.
Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.
Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.



Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.
Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.
Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).



Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.
Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.
Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

GYSFLASH Pb / LITHIUM

ELECTRO MOBILITY CHARGERS
Pb / Lithium

LiFePO₄ / Li-ion / Li-Po /
NMC / LCO / MCO / NCA...



24 V • ELECTRICAL MOBILITY

GYSFLASH 6.24 PL

6 A **GO > 2 V**

GO > 2 V SSM Auto Recovery Temperature

7 STEP Pb 8 STEP LiFePO₄ 8 STEP Li-ion

S SAE Connector

1.45 m 0.45 m 0.45 m

027398



48 • INDUSTRY / ELECTROMOBILITY

GYSFLASH 3.48 PL

3 A


GO > 5 V SSM Auto Recovery Temperature

7 STEP Pb 8 STEP LiFePO₄ 8 STEP Li-ion

S SAE Connector

1.45 m 0.45 m

027893



OPTION

Magnetfix 20 026063

x4



36 / 48 • INDUSTRY / ELECTROMOBILITY

GYSFLASH 10.36/48 PL

10 A

GO > 5 V SSM Auto Recovery Temperature

7 STEP Pb 8 STEP LiFePO₄ 8 STEP Li-ion

A ANDERSON Connector

1.9 m (4 mm²)

027060



ELECTROMOBILITY

MOBILITY



OUTDOOR



INDUSTRY



MEDICAL




SMART CHARGE

7 STEP / 8 STEP


Pb

1. Status analysis
2. Recovery
3. Test desulphation
4. Desulphation
5. Fast charge 80%
6. Absorption
7. Floating 100%



LiFePO₄ (LFP) / Li-ion

1. UVP Wake up - Status analysis
2. Recovery
3. Fast charge 90%
4. Absorption 95%
5. Test
6. Completion
7. Equalization
8. Floating 100%



UVP Wake up (Under Voltage Protection)
Battery reactivation when in UVP protection.
Réactivation de la batterie en protection UVP.
Reaktivierung der Batterie mit UVP-Schutz.

Equalizing Balancing System
Balancing of the battery cells.
Équilibrage des cellules.
Ausgleich der Batteriezellen.

DESIGN GYS FRANCE	PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN	50 / 60 Hz	Power	I _{charge}	V	n cell			Charge	Maintenance	Z _z	Ondulation/Ripple	Charging curve	IP	Weight	Dimensions	L x W x H cm / kg
						Pb	LFP	NMC									
MADE IN GYS CHINA				6 A	24 V	12	8	6	15 > 125 Ah (Pb) 2 > 125 Ah (Li)	15 > 170 Ah (Pb) 2 > 170 Ah (Li)	<0.4 Ah /month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 65	1,1 kg	22.1 x 11.1 x 5.8 cm / 1.4
									6 > 60 Ah (Pb) 3 > 60 Ah (Li)	6 > 60 Ah (Pb) 3 > 60 Ah (Li)	<0.4 Ah /month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 65	1,1 kg	22.1 x 11.1 x 5.8 cm / 1.2
MADE IN FRANCE				10 A	36 V	18	12	9	20 > 230 Ah (Pb) 10 > 230 Ah (Li)	20 > 230 Ah (Pb) 10 > 230 Ah (Li)	<0.4 Ah /month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 31	1,85 kg	19 x 19 x 7.3 cm / 2
					48 V	24	15/16	13/14	15 > 160 Ah (Pb) 8 > 160 Ah (Li)	15 > 160 Ah (Pb) 8 > 160 Ah (Li)	<0.4 Ah /month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 31	1,85 kg	19 x 19 x 7.3 cm / 2



F Flash Connector GYSFLASH ≤ 6A : 1.12 / 4.12 / 6.12 / 6 Heritage / 6.24 / 1.12 Li / 6.12 Li / 1.12 PL

F1 / Clamps L 0.45 m (1.3 mm²) All 026889	F2 / Charge indicator L 0.56 m (1.3 mm²) All 12V LEAD 029149	F3 / Eyelets ø M6 L 0.45 m (1.3 mm²) All 12V 029194 ø M8 L 0.45 m (1.3 mm²) 24V 36V 48V 027626	F4 / Charge indicator eyelets ø M6 L 0.56 m (1.3 mm²) All 12V LEAD 029200	F5 / Cigarette lighter L 0.45 m (0.82 mm²) 029439	F6 / Cable L 2.50 m (1.3 mm²) All 029057	F7 / Connector MLX L 0.45 m (1.3 mm²) 027589	F8 Adapter S / F - F / S L 0.45 m (1.3 mm²) 027480	F9 Adapter F / A L 0.45 m (1.3 mm²) 025820

s SAE Connector GYSFLASH < 16A : 8.12 PL / 12.12 / 9.24 / 6.24 / 3.48 PL

S1 / Clamps L 1.50 m (1.3 mm²) All +Showroom Gysflash 1212 027688	S2 / Eyelets ø M6 L 0.45 m (1.3 mm²) 12V 24V 027466 ø M8 L 0.45 m (1.3 mm²) 24V 36V 48V 027633 ø M10 L 0.45 m (1.3 mm²) 36V 48V 027640	S3 / XLR 3 pin L 0.45 m (1.3 mm²) 027428	S4 / T-Bar L 0.45 m (1.3 mm²) 027442	S5 Adapter S / A L 0.45 m (1.3 mm²) 027473	S6 KIT SAE / JACK (max 5 A) L 0.45 m (1.3 mm²) 025646	S7 / Cigarette lighter (max 10 A) Only for 8.12 PL L 0.45 m (1.3 mm²) 077331	S8 / Cable L 2.5 m (1.3 mm²) 077348

A ANDERSON Connector GYSFLASH < 40A : 18.12 PL / 30.12 PL / 20.12-24 PL / 10.36-48 PL

A1 / Clamps All L 1.90 m (4 mm²) 026094 L 6 m (4 mm²) 027435	A2 / Eyelets 4 mm² ø M6 L 0.40 m 12V 24V 027657 ø M8 L 0.40 m 24V 36V 48V 027664 ø M8 L 1.90 m 24V 36V 48V 027794 ø M10 L 0.40 m 36V 48V 027671	A3 / Anderson L 1.5 m (4 mm²) 027855

XTREM CABLES GYSFLASH 15.24 XTREM

2pts/NATO Spiral 5 m 028968	2pts/NATO 5 m - 4 mm² 025837	2pts/DIN14690 Emergency vehicle 5 m 028777

GYSFLASH						MEDICAL SERVICE - LEISURE				MOTORBIKE LIGHT MOBILITY				AUTO - CAMPER VAN - TRUCK								MARINE				INDUS TRY	URBAN
	6V	12V	24V	36V	48V																						

Pb																											
1.12																											
1.12 PL																											
4.12																											
6.12																											
8.12																											
8.12 PL																											
12.12																											
18.12 PL																											
30.12 PL																											
6 Heritage	6V	12V																									
6.24 PL			24V																								
20.12/24 PL			12V 24V																								
6.24																											
9.24			6V 12V 24V																								
3.48 PL																											
10.36/48 PL																											

LiFePO4																											
1.12 Lithium																											
1.12 PL																											
6.12 Lithium																											
8.12 PL																											
18.12 PL																											
30.12 PL																											
6.24 PL																											
20.12/24 PL																											
3/48 PL																											
10.36/48 PL																											

Li-ion																											
6.24 PL																											
3/48 PL																											
10.36/48 PL																											

M = maintenance only



GYSFLASH PRO

BSU

BATTERY SUPPORT UNITS

Battery support for:

- ✓ Diagnostics
- ✓ ECU programming
- ✓ ADAS recalibration



NEW DESIGN 2026



OLD DESIGN



YouTube
PLAYLIST
GYSFLASH PRO

✓ SHOWROOM



10.5 cm



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026



22 languages

GB DK CZ
FR FI PL
DE TR SK
NL HR UA
ES GR
PT HU
IT CN simplified
RU CN traditional
SE JP

PFC POWER FACTOR CORRECTION

FV FLEXIBLE VOLTAGE
85 V 265 V



21

GYSFLASH PRO

BATTERY SUPPORT UNITS



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026



NEW DESIGN
01 / 2026

12 V

GYSFLASH 30.12

30 A

PFC SC

2,5 m - 6 mm²
029224



GYSFLASH 50.12 FV

50 A

PFC FV SC

2,5 m - 10 mm²
026056



GYSFLASH 100.12

100 A

PFC SC

2,5 m - 16 mm²
029071

029453



5 m - 16 mm²
029415
029002
082304

6 / 12 / 24 V

GYSFLASH 30.24

30 A

PFC SC

2,5 m - 6 mm²
029231



GYSFLASH 50.24

50 A

PFC SC

2,5 m - 10 mm²
029095
5 m - 10 mm²
029620



GYSFLASH 102.12

100 A

PFC SC

5 m - 16 mm²
029606
082311



INCLUDED

Fixing kit
for Gysflash 102.12



SC

SMART COOLING TECHNOLOGY


100% DUST PROOF



SILENT


SMART PB & LiFePO₄

Pb : 8-step



1. Status analysis
2. Recovery
3. Sulphation test
4. Desulphation
5. Fast charge 80%
6. Absorption
7. Refresh
8. Floating 100%

LiFePO₄ : 7-step



1. Status analysis
2. Recovery
3. Fast charge 90%
4. Absorption 95%
5. Completion
6. Equalization
7. Floating 100%

CHARGE

Pb AUTOMOTIVE

- ✓ GEL
- ✓ AGM
- ✓ LIQUID
- ✓ EASY
- ✓ EXPERT

Pb TRACTION

- ✓ GEL
- ✓ LIQUID

LITHIUM READY

- ✓ LFP/LiFePO₄

BSU

DIAG +



U2 ADJUSTABLE

SHOWROOM



CHANGE BATTERY



POWER SUPPLY



U2 & I2 max ADJUSTABLE

MADE IN FRANCE

MADE IN FRANCE	 50 / 60 Hz				I max	25°C @ 100 %	40°C @ 100 %		START MINI	IP	 TRACTION BATTERIES	 L 	 mm²	 SHOWROOM CONNECT			 L × W × H cm / kg
GYSFLASH 30.12	220 › 240 V	540 W	2.5 m	12 V	30 A	30 A	30 A	10 › 400 Ah	2 V	21	—	2,5 m	6	Ø M6	2.8 kg	25.5 × 10.5 × 23 cm	41.4 × 31.1 × 25 / 4.9
GYSFLASH 50.12 FV	100 › 240 V	850 W	2.5 m	12 V	50 A	50 A	40 A	10 › 600 Ah	2 V	21	—	2,5 m	10	Ø M6	4.4 kg	30 × 10.5 × 29.2 cm	41 × 39 × 22.5 / 6.5
GYSFLASH 100.12	220 › 240 V	1600 W	2.5 m	12 V	100 A	75 A	66 A	20 › 1200 Ah	2 V	21	—	2,5 m 5 m	16	Ø M6	4.7 kg	32 × 10.5 × 29.2 cm	41 × 39 × 22.5 / 7.2 41 × 39 × 22.5 / 8
GYSFLASH 30.24	220 › 240 V	540 W	2.5 m	6 V/12 V 24 V	30 A 15 A	30 A 15 A	30 A 15 A	10 › 400 Ah	2 V	21	●	2,5 m	6	Ø M6	2.8 kg	25.5 × 10.5 × 23 cm	41.4 × 31.1 × 25 / 4.9
GYSFLASH 50.24	220 › 240 V	1600 W	2.5 m	6 V/12 V 24 V	50 A	50 A 45 A	50 A 45 A	10 › 600 Ah	2 V	21	●	2,5 m 5 m	10	Ø M6	4.4 kg	30 × 10.5 × 29.2 cm	41 × 39 × 22.5 / 6.5 41 × 39 × 22.5 / 7.9
GYSFLASH 102.12	220 › 240 V	1600 W	2.5 m	12 V	100 A	75 A	66 A	20 › 1200 Ah	2 V	21	—	5 m	16	Ø M6	5.5 kg	34.4 × 29.1 × 12 cm	41 × 39 × 22.5 / 8.7



GYSFLASH PRO CNT

BSU

BATTERY SUPPORT UNITS

Battery support for:

- ✓ Diagnostics
- ✓ ECU programming
- ✓ ADAS recalibration

12 V (factory preset)
16/24 V READY

Use custom configuration tool
(detail p.34)



NEW DESIGN
01 / 2026



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026



NEW
DESIGN
2026



OLD DESIGN

CNT

Connected
Technology

FULLY
CUSTOMIZABLE
p.34



22 languages

GB DK CN simplified
FR FI CN traditional
DE TR JP
NL HR
ES GR
PT CZ
IT PL
RU SK
SE UA
HU

FV FLEXIBLE
VOLTAGE

85 V 265 V
110 V 230 V

PFC POWER FACTOR
CORRECTION

16 V

COMPATIBLE WITH
16V BATTERIES

✓ SHOWROOM



10.5 cm
51.12 CNT
101.12 CNT

13 cm
121.12 CNT FV
125.12 CNT FV
101.24 CNT FV
51.48 CNT FV



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026



NEW DESIGN
02 / 2026

12 V

GYSFLASH 51.12 CNT FV

50 A

PFC FV SC CNT

2,5 m - 10 mm²
068179



GYSFLASH 101.12 CNT FV

100 A

PFC FV SC CNT

2,5 m - 16 mm²
025790

5 m - 16 mm²
026988



GYSFLASH 121.12 CNT FV

120 A

PFC FV CNT

5 m - 25 mm²
026971

027756 071605 082298

no accessories
027923



GYSFLASH 125.12 CNT FV

120 A 120 A @ 100%

PFC FV CNT

5 m - 25 mm²
028883

082274



6 / 12 / 16 / 24 V

GYSFLASH 101.24 CNT FV

100 A

PFC FV CNT

16 V

5 m - 25 mm²
025967



6 / 12 / 16 / 24 / 36 / 48 V

GYSFLASH 51.48 CNT FV

50 A

PFC FV CNT

16 V

5 m - 10 mm²
072015



SC

SMART
COOLING
TECHNOLOGY


100%
DUST
PROOF



SILENT



SMART 9 STEP



CHARGE (150 CURVE CAPACITY)

- Pb AUTOMOTIVE
 - ✓ GEL
 - ✓ AGM
 - ✓ LIQUID
 - ✓ EASY
 - ✓ NORMAL
 - ✓ BOOST
 - ✓ RECOVERY+
 - ✓ and more
- Pb TRACTION
 - ✓ GEL
 - ✓ LIQUID
 - ✓ and more
- LITHIUM
 - ✓ LFP/LiFePO₄
 - ✓ LI-ION STD
 - ✓ LFP CELL+
 - ✓ LI-ION CELL+
 - ✓ and more

BSU (10 CURVE CAPACITY)

- DIAG +
- SHOWROOM
- CHANGE BATTERY
- POWER SUPPLY
- AND MORE
- ✓ TEST
 - ✓ VOLTAGE
 - ✓ START UP
 - ✓ ALTERNATOR
- ✓ STARTER
 - ✓ START

Connected Modules & Technology p.36



MADE IN FRANCE

MADE IN FRANCE	 50 / 60 Hz			 I max	25°C @ 100 %	40°C @ 100 %		START MINI	IP	 L	 mm²	 TRACTION BATTERIES	 SHOWROOM CONNECT			 L × W × H cm / kg	
GYSFLASH 51.12 CNT FV	220 > 240 V	1600 W	2.5 m	12V	50 A	230 V : 50 A 110 V : 40 A	230 V : 40 A 110 V : 27 A	10 > 600 Ah	1 V	41	2,5 m	10	●	Ø M6	4,6 kg	30 × 10,5 × 29,2 cm	41 × 39 × 22,5 / 6,8
	100 > 127 V	800 W		24V	230 V : 50 A 110 V : 25 A	230 V : 44 A 110 V : 25 A	230 V : 35 A 110 V : 22 A										
GYSFLASH 101.12 CNT FV	220 > 240 V	1600 W	2.5 m	12V	230 V : 100 A 110 V : 50 A	230 V : 75 A 110 V : 45 A	230 V : 66 A 110 V : 40 A	20 > 1200 Ah	1 V	21	2,5 m 5 m	16	●	Ø M6	5,1 kg	32 × 10,5 × 29,2 cm	41 × 39 × 22,5 / 7,5 41 × 39 × 22,5 / 8,6
	100 > 127 V	800 W															
GYSFLASH 121.12 CNT FV	220 > 240 V	2000 W	2.5 m	12V	230 V : 120 A 110 V : 100 A	230 V : 110 A 110 V : 75 A	230 V : 90 A 110 V : 55 A	20 > 1500 Ah	1 V	20	5 m	25	●	Ø M6	5,9 kg	32,5 × 13 × 27,2 cm	41 × 39 × 22,5 / 10,4
	100 > 127 V	1500 W															
GYSFLASH 125.12 CNT FV	220 > 240 V	2000 W	2.5 m	12V	230 V : 120 A 110 V : 100 A	230 V : 120 A 110 V : 100 A	230 V : 116 A 110 V : 77 A	20 > 1500 Ah	1 V	40	5 m	25	●	Ø M6	6,3 kg	33,4 × 13 × 28 cm	41 × 39 × 22,5 / 10,8
	100 > 127 V	1500 W															
GYSFLASH 101.24 CNT FV	220 > 240 V	3200 W	2.5 m	6/12V	100 A	110 V : 72 A 230 V : 89 A	110 V : 47 A 230 V : 68 A	20 > 1200 Ah	1 V	20	5 m	25	●	Ø M6	6 kg	32,5 × 13 × 27,2 cm	41 × 39 × 22,5 / 10,5
	100 > 127 V	1500 W		24V	230 V : 100 A 110 V : 50 A	230 V : 76 A 110 V : 50 A	230 V : 59 A 110 V : 35 A										
GYSFLASH 51.48 CNT FV	220 > 240 V	3200 W	2.5 m	6/12/24V	50 A	110 V : 49 A 110 V : 44 A	230 V : 39 A 110 V : 21 A	10 > 600 Ah	1 V	20	5 m	10	●	Ø M6	5,6 kg	32,5 × 13 × 27,2 cm	41 × 39 × 22,5 / 9
	100 > 127 V	1500 W		36/48V	230 V : 50 A 110 V : 25 A	230 V : 45 A 110 V : 26 A	230 V : 35 A 110 V : 19 A										



GYSFLASH PRO CNT

BSU

BATTERY SUPPORT UNITS

Battery support for:

- ✓ Diagnostics
- ✓ ECU programming
- ✓ ADAS recalibration




22 languages

GB NL IT DK HR PL UA CN simplified
FR ES RU FI GR SK CN traditional
DE PT SE TR CZ HU JP



INCLUDED


Fixing kit



OPTIONS


Magnetfix 50

029637



GYSFLASH PRO vertical wall mounting kit

082694



CNT

Connected Technology

FULLY CUSTOMIZABLE

p.34

PFC POWER FACTOR CORRECTION

16 V COMPATIBLE WITH 16V BATTERIES

FV FLEXIBLE VOLTAGE

85 V 265 V

12 V

GYSFLASH 103.12 CNT FV

100 A

PFC FV SC CNT

5 m - 16 mm²
072008



GYSFLASH 123.12 CNT FV

120 A

PFC FV CNT

5 m - 25 mm²
025677



6 / 12 / 16 / 24 V

GYSFLASH 53.24 CNT FV

50 A

PFC FV CNT SC 16 V

5 m - 10 mm²
082540



GYSFLASH 103.24 CNT FV

100 A

PFC FV CNT 16 V

5 m - 25 mm²
025684



SC


SMART COOLING TECHNOLOGY

100% DUST PROOF



SILENT

SMART 9 STEP



CHARGE (150 CURVE CAPACITY)

- Pb AUTOMOTIVE**
 - ✓ GEL
 - ✓ AGM
 - ✓ LIQUID
 - ✓ EASY
 - ✓ NORMAL
 - ✓ BOOST
 - ✓ RECOVERY+ and more
- Pb TRACTION**
 - ✓ GEL
 - ✓ LIQUID
 - ✓ EASY
- LITHIUM**
 - ✓ LFP/LiFePO₄
 - ✓ LI-ION STD
 - ✓ LFP CELL+
 - ✓ LI-ION CELL+ and more

BSU (10 CURVE CAPACITY)

- DIAG +**
 - U2 ADJUSTABLE
- CHANGE BATTERY**
 - U2 & I2 max ADJUSTABLE
- POWER SUPPLY**
 - U2 & I2 max ADJUSTABLE
- AND MORE**
- ✓ TEST**
 - ✓ VOLTAGE
 - ✓ START UP
 - ✓ ALTERNATOR
- ✓ STARTER**
 - ✓ START

CNT

Connected Modules & Technology p.36



MADE IN FRANCE

MADE IN FRANCE	 50 / 60 Hz			 I max	 25°C @100 %	 40°C @ 100 %		 START MINI	 IP	 L ↕	 mm²	 TRACTION BATTERIES	 SHOWROOM CONNECT			 L × W × H cm / kg	
GYSFLASH 103.12 CNT FV	220 ÷ 240 V 100 ÷ 127 V	1600 W 800 W	2.5 m	12 V	230 V : 100 A 110 V : 50 A	230 V : 75 A 110 V : 50 A	230 V : 66 A 110 V : 40 A	20 ÷ 1200 Ah	1 V	21	5 m	16	—	Ø M6	5.8 kg	34,4 × 29.1 × 12 cm	41 × 39 × 22.5 / 9.2
GYSFLASH 123.12 CNT FV	220 ÷ 240 V 100 ÷ 127 V	2000 W 1500 W		12 V	230 V : 120 A 110 V : 100 A	230 V : 120 A 110 V : 100 A	230 V : 120 A 110 V : 85 A	20 ÷ 1500 Ah	1 V	30	5 m	25	●	Ø M6	6.4 kg	34 × 25.4 × 15 cm	41 × 39 × 22.5 / 11
GYSFLASH 53.24 CNT FV	220 ÷ 240 V 100 ÷ 127 V	1600 W 800 W	2.5 m	12 V	50 A	230 V : 50 A 110 V : 40 A	230 V : 41 A 110 V : 27 A	10 ÷ 600 Ah	1 V	21	5 m	10	●	Ø M6	5,5 kg	34,4 × 29.1 × 12 cm	41 × 39 × 22.5 / 8.6
				24 V	230 V : 50 A 110 V : 25 A	230 V : 44 A 110 V : 25 A	230 V : 35 A 110 V : 22 A										
GYSFLASH 103.24 CNT FV	220 ÷ 240 V 100 ÷ 127 V	3200 W 1500 W	2.5 m	6/12 V	100 A	100 A	230 V : 79 A 110 V : 68 A	20 ÷ 1200 Ah	1 V	30	5 m	25	●	Ø M6	6.4 kg	34 × 25.4 × 15 cm	41 × 39 × 22.5 / 11
				24 V	230 V : 100 A 110 V : 50 A	230 V : 95 A 110 V : 50 A	230 V : 72 A 110 V : 47 A										



25

GYSFLASH PRO CNT

BATTERY SUPPORT UNITS



GYSFLASH PRO CNT

BSU

BATTERY SUPPORT UNITS

Battery support for:

- ✓ Diagnostics
- ✓ ECU programming
- ✓ ADAS recalibration

CNT
Connected
Technology

**FULLY
CUSTOMIZABLE**
p.34

FV FLEXIBLE
VOLTAGE
85 V ← 265 V
110 V 230 V

PFC POWER FACTOR
CORRECTION

16 V ✓ COMPATIBLE WITH
16V BATTERIES



19
languages

GB FI
FR TR
DE HR
NL GR
ES CZ
PT PL
HU SK
IT UA
RU
SE
DK



NEW
03 / 2026

6 / 12 / 16 / 24V

12V

GYSFLASH 107.24 CNT FV

100 A

PFC FV CNT 16 V ✓

5 m - 25 mm²
082939



GYSFLASH 157.12 CNT FV

150 A

PFC FV CNT

089969



SC


**SMART
COOLING
TECHNOLOGY**

100%
DUST
PROOF



SILENT

SMART 9 STEP



CHARGE (150 CURVE CAPACITY)

Pb AUTOMOTIVE

- ✓ GEL
- ✓ AGM
- ✓ LIQUID
- ✓ EASY
- ✓ NORMAL
- ✓ BOOST
- ✓ RECOVERY+
- ✓ and more


Pb TRACTION

- ✓ GEL
- ✓ LIQUID
- ✓ and more

LITHIUM

- ✓ LFP/LiFePO₄
- ✓ LI-ION STD
- ✓ LFP CELL+
- ✓ LI-ION CELL+
- ✓ and more

BSU (10 CURVE CAPACITY)



✓ **TEST**

- ✓ VOLTAGE
- ✓ START UP
- ✓ ALTERNATOR

✓ **STARTER**

✓ START

INCLUDED

Fixing kit



OPTIONS



GYSFLASH PRO vertical
wall mounting kit
082694



22 languages

GB NL IT DK HR PL UA CN simplified
FR ES RU FI GR SK CN traditional
DE PT SE TR CZ HU JP



NEW DESIGN
06 / 2026



old design



NEW DESIGN
01 / 2026

6 / 12 / 16 / 24 / 36 / 48V

GYSFLASH 25.48 CNT FV

25 A

PFC SC FV CNT 16 V ✓

5 m - 10 mm²
075962



GYSFLASH 53.48 CNT FV

50 A

PFC FV CNT 16 V ✓

5 m - 10 mm²
025998



CNT

Connected
Modules
& Technology
p.36



MADE IN FRANCE	 50 / 60 Hz			I max	25°C @ 100 %	40°C @ 100 %		START MINI	IP		 mm²	 TRACTION BATTERIES	 SHOWROOM CONNECT			 L × W × H cm / kg	
GYSFLASH 107.24 CNT FV	220 ÷ 240 V	3200 W	2.5 m	6/12 V	100 A	100 A	230 V : 79 A 110 V : 68 A	20 ÷ 1200 Ah	1 V	30	5 m	25	●	Ø M6	6.4 kg	34 × 25.4 × 15 cm	41 × 39 × 22.5 / 11
	100 ÷ 127 V	1500 W		24 V	230 V : 100 A 110 V : 50 A	230 V : 95 A 110 V : 50 A	230 V : 72 A 110 V : 47 A										
GYSFLASH 157.12 CNT FV	220 ÷ 240 V	2500 W	2.5 m	12 V	230 V : 150 A 110 V : 100 A	230 V : 120 A 110 V : 100 A	230 V : 116 A 110 V : 77 A	20 ÷ 1800 Ah	1 V	40	5 m	25	●	Ø M6	ND	33.4 × 13 × 28 cm	41 × 39 × 22.5 / ND
	100 ÷ 127 V	1500 W															
GYSFLASH 25.48 CNT FV	220 ÷ 240 V	1600 W	2.5 m	6/12/24 V	25 A	230 V : 24 A 110 V : 19 A	230 V : 22 A 110 V : 12 A	10 ÷ 300 Ah	1 V	21	5 m	10	●	Ø M6	5,5 kg	34.4 × 29.1 × 12 cm	41 × 39 × 22.5 / 8.8
	100 ÷ 127 V	800 W		36/48 V	230 V : 25 A 110 V : 12 A	230 V : 24 A 110 V : 12 A	230 V : 20 A 110 V : 10 A										
GYSFLASH 53.48 CNT FV	220 ÷ 240 V	3200 W	2.5 m	6/12/24 V	50 A	50 A	230 V : 41 A 110 V : 28 A	10 ÷ 600 Ah	1 V	30	5 m	10	●	Ø M6	5,9 kg	34 × 25.4 × 15 cm	41 × 39 × 22.5 / 9.5
	100 ÷ 127 V	1500 W		36/48 V	230 V : 50 A 110 V : 25 A	230 V : 48 A 110 V : 26 A	230 V : 37 A 110 V : 20 A										



27

GYSFLASH PRO CNT

BATTERY SUPPORT UNITS



STARTFLASH

BSU BATTERY SUPPORT UNIT & STARTER

CNT Connected Technology

Battery support for:

- ✓ Diagnostics
- ✓ ECU programming
- ✓ ADAS recalibration


SPECIAL PROJECTS

Contact us for special projects.

Quick Customization:
Modes, Curves, parameters...

19 languages

GB RU GR
FR SE CZ
DE DK PL
NL FI SK
ES TR UA
PT HR
IT HU



4 in 1

AUTOMATIC CHARGE

Pb AUTOMOTIVE

- ✓ GEL
- ✓ AGM
- ✓ LIQUID
- ✓ EASY
- ✓ EXPERT
- ✓ NORMAL
- ✓ BOOST
- ✓ RECOVERY+

Pb TRACTION

- ✓ GEL
- ✓ LIQUID

LITHIUM READY

- ✓ LFP/LiFePO₄
- ✓ LI-ION STD
- ✓ LFP CELL+
- ✓ LI-ION CELL+

BSU

DIAG +



SHOWROOM



CHANGE BATTERY



POWER SUPPLY



AUTOMATIC STARTER

- ✓ START


TEST

- ✓ VOLTAGE
- ✓ START UP
- ✓ ALTERNATOR


CNT

Connected Technology


SOFTWARE UPDATE



CUSTOMIZATION





TRACEABILITY



Connected Modules & Technology p.36



SMART 9 STEP



- FULL PROTECTION**
 - On-board electronics
 - Over voltage
 - No sparks

- UNIVERSAL MODE** **AUTO SELECTION**
- SULFATED BATTERIES**
- START STOP** **ALL BATTERIES**
- GO** **>1V**

PFC POWER FACTOR CORRECTION
185 V ← 265 V
110 V 220 V

1 WORLD FIRST
Inverter Pb & Li All-in-one



6/12/16/24V

STARTFLASH 120.24 CNT

2, 300 A

5 m - 25 mm² 700 A
073616

OPTION

Trolley 074965



STARTER RECOMMENDATION	6V 12V 24V			5 Ah	6V	+300 Ah
	6V	12V	24V			
STARTFLASH 120	•	•	•	10 • 180 Ah	180 • 250 Ah	

MADE IN FRANCE	 50 / 60 Hz	CHARGE 							START 			IP	 LxWxH cm / kg	 LxWxH cm / kg		
				START MINI	I max	25°C @ 100 %	40°C @ 100 %		 TRACTION BATTERIES		1V/C				0V/C	AUTO START
STARTFLASH 120.24 CNT	85 > 265 V	6/12/24V	3500 W	2 V	110 V : 100 A	75 A	55 A	20 · 1200Ah	●	6/12/24V	150 A	150 A	●	20	49 x 37.5 x 30.5 / 14	41.5 x 32.5 x 25.5 / 18.5
					230 V : 120 A	110 A	90 A			6V :	300 A	300 A				
										12 V :	300 A	300 A				
										24 V :	200 A	300 A				





BSU

BATTERY
SUPPORT UNITSCNT
Connected
TechnologyYouTube
VIDEO
EQUALIZE MODEBROCHURE
BATTERY
BALANCING

EQUALIZE MODE

REBALANCE YOUR BATTERY PACK



BENEFITS

Increased
reliabilityHealthy
batteriesWaste
reduction

EQUALIZATION & BSU

Use all your BSU modes while balancing the batteries

DIAG +

U2
ADJUSTABLE


SHOWROOM



CHANGE BATTERY




POWER SUPPLY

U2 & I2 max
ADJUSTABLE


AND MORE

SMART 9 STEP CHARGE

Pb



1. Status analysis
2. Recovery
3. Sulphation test
4. Desulphation
5. Fast charge 80%
6. Absorption
7. Test Absorption
8. Refresh
9. Floating 100%

LiFePO₄

UVP Wake up (Under Voltage Protection). Battery reactivation when in UVP protection

EBS
Equalizing Balancing System
100% Perfect charge

1. Status analysis
2. UVP Wake Up
3. Recovery
4. Fast charge 90%
5. Absorption 95%
6. Test
7. Completion
8. Equalization
9. Floating 100%

GYSFLASH EQUALIZE PACKS



NEW

EQUALIZE (2 × 12 V CHARGERS)



Gysflash 101.12 CNT FV

026988

12 V



Gysflash 101.12 CNT FV

026988

12 V



CNT SHM

025981



SMC Cable (1m)

056596

BSU Flash Plus
085510pack EQUALIZE 1
085534pack EQUALIZE 2
085541

EQUALIZE (2 × 24 V CHARGERS)



Gysflash 101.24 CNT FV

025967

24 V



Gysflash 101.24 CNT FV

025967

24 V



CNT SHM

025981



SMC Cable (1m)

056596

BSU Flash Plus
085510pack EQUALIZE 3
085558pack EQUALIZE 4
085565

CNT

Connected
Modules
& Accessories
p.36

BSU

BATTERY
SUPPORT UNITS

CNT
Connected
Technology




FULLY
CUSTOMIZABLE
p.34



19 languages

GB	ES	RU	TR	PL
FR	PT	SE	HR	SK
DE	HU	DK	GR	UA
NL	IT	FI	CZ	

SPECIAL PROJECT
- CONTACT US



CHARGE (150 CURVE CAPACITY)

Pb CHARGE

LEAD ACID
and more

Li CHARGE

LITHIUM
and more

SUPPLY (10 CURVE CAPACITY)

EPS (External Power Supply)

and more

POWER-UP

LITHIUM
REACTIVATION MODE

CONFIG DESIGNER MENU

Setting the charge curve from the Gysflash interface :

U _{esp}	11.5 V
U _{lade}	14.8 V
I _{lade}	150.0 A
I _{ehl}	2.5 A
T _{min}	00:05:00
T _{max}	65:00:00
Q _{max}	250 Ah
T/Q _{max} error	EHL
U _{ehl}	13.2 V
T _{ges}	250:00:00
U _{low}	5.0 V

SECURE ACCESS

- Customizable manual accesses
- Configurable password



PFC POWER FACTOR
CORRECTION

FV FLEXIBLE
VOLTAGE

85 V 265 V

110 V 230 V


GYSFLASH 108.12 CNT FV
GYSFLASH 148.12 CNT FV

FV FLEXIBLE
VOLTAGE

320V 520V

400 V 480 V

GYSFLASH 158.12 CNT FV



ACCESSORIES p.39



12 V




296

145 mm

376

Plug C14




296

145 mm

376

Plug C20



380

145 mm

376

GYSFLASH 108.12 CNT FV

105 A

PFC SC FV CNT

no accessories
085602

GYSFLASH 148.12 CNT FV

145 A

PFC SC FV CNT

no accessories
069916

GYSFLASH 158.12 CNT FV

150 A

SC FV CNT

no accessories
069909

MADE IN FRANCE	 50 / 60 Hz			 I max	25°C @100 %	40°C @ 100 %	60°C @ 100 %		START MINI	IP			
GYSFLASH 108.12 CNT FV	220 V : 240 V	1800 W	2.5 m	12 V	230 V : 105 A 110 V : 65 A	230 V : 105 A 110 V : 65 A	230 V : 105 A 110 V : 65 A	230 V : 88 A 110 V : 62 A	20 > 1200 Ah	1 V	54	9.4 kg	37.6 × 14.5 × 29.6 cm
	100 > 127 V	1000 W			230 V : 145 A 110 V : 100 A	230 V : 134 A 110 V : 100 A	230 V : 116 A 110 V : 90 A	230 V : 88 A 110 V : 62 A					
GYSFLASH 148.12 CNT FV	220 V : 240 V	2500 W	2.5 m	12 V	230 V : 145 A 110 V : 100 A	230 V : 134 A 110 V : 100 A	230 V : 116 A 110 V : 90 A	230 V : 88 A 110 V : 62 A	20 > 1800 Ah	1 V	54	9.4 kg	37.6 × 14.5 × 29.6 cm
	100 > 127 V	1500 W											
GYSFLASH 158.12 CNT FV	380 > 500 V	2500 W	-	12 V	150 A	140 A	120 A	100 A	20 > 1800 Ah	1 V	54	10.3 kg	37.6 × 14.5 × 38 cm



BSU

BATTERY SUPPORT UNITS

CNT
Connected
Technology




SOFTWARE UPDATE

LIFETIME EVOLUTIONS



TRACEABILITY

CHARGING DATA



DESIGN YOUR CHARGING CURVE

PRODUCT CONFIGURATIONS


CNT MANAGER (gys.fr)

- GYSFLASH parameters
- Custom curves
- Multi-unit management
- Import/export configurations
- ...



Full customisation

Create your personalised configuration



Adjust your unit to best suit your application

	LEAD-ACID - PB	Lithium - LFP	Lithium - Li-ion std
CELL VOLTAGE (20% - 100%)	2.0 V/cell – 2.15 V/cell	3.2 V/cell – 3.6 V/cell	3.5 V/cell – 4.2 V/cell
CHARGING VOLTAGE	2.33 V/cell – 2.47 V/cell	3.6 V/cell	4.2 V/cell
Gysflash xx.12 CNT	1 S* – 6 S	1 S – 4 S	1 S – 3 S
Gysflash xx.24 CNT	1 S – 12 S	1 S – 8 S	1 S – 7 S
Gysflash xx.48 CNT	1 S – 24 S	1 S – 16 S	1 S – 14 S

*S = Battery serial cells

Download one of our GYS configurations

Configuration file (gys.fr)	Applications	CHARGE MODE											POWER MODE						MISCELLANEOUS			
		Pb-CHARGE						Li-CHARGE			TRACTION		SHOWROOM	DIAG+	CHANGE BAT.	STARTER MODE	POWER SUPPLY	Li-SUPPLY/LFP	Li-SUPPLY/Li-Ion	TESTER MODE		
		normal	AGM	liquid	Easy	Boost	Recovery +	Ca / Ca recov	LFP/LiFePO4	Li-ion std	LFP cell+	Li-ion cell+									liquid	gel
1_gys_original.gfc	Initial configuration of the charger	✓	✓	✓	✓				✓						✓	✓						✓
2_car_extended.gfc	Extensive features for garages	✓	✓	✓	✓	✓	✓	✓							✓	✓	✓	✓	✓			✓
3_showroom_only.gfc	Simplified version for dealerships and demonstration vehicles														✓							
4_pro_lithium.gfc	Professional of lithium battery								✓	✓	✓	✓						✓	✓	✓		
5_traction.gfc	Forklift truck, electric pallet truck, stacker...												✓	✓								
6_full_version.gfc	Full version	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



YouTube
PLAYLIST
CNT TECHNOLOGY



Contact us for special projects.

Quick Customization:
Modes, Curves, parameters...

MODULES

MAXIMUM VERSATILITY

SINGLE MODULE




MULTI-MODULE



ADVANCED




MULTI-MODULE GROUPS




PARALLEL CHARGING

EXAMPLE : GYSFLASH 101.12 CNT (X4)



PORTABLE BSU



USAGE DURATION Power pack + Gysflash	GYSFLASH			
	30.12 / 30.24	50.12 / 51.12	100.12 / 103.12 / 50.24 / 53.24 / 25.48	121.12 / 123.12 / 125.12
POWER PACK 520	1 h 10	—	—	—
POWER PACK 14.22	3 h 10	1 h 50	1 h	45 min
POWER PACK 14.15 FC	3 h 10	1 h 50	1 h	—





CNT TECHNOLOGY MODULES

CNT Connected Technology

SMC CABLE

1 m 056596 3 m 025691



YouTube
PLAYLIST
CNT TECHNOLOGY

COMING SOON



SCAN

CRIT'AIR



Customer data



Battery data



Charge data



USB Barcode scanner

1D/2D

027718



USB direct connection



Wireless Barcode reader

1D/2D

086869

Wireless



Download Brochure
Télécharger la brochure



OPTIONS

Barcode scanner support
025745



LIGHT & SOUND



Scratch mounted

CNT-SLM Smart Light Module

027978
↓ 12.6 × 14.6 × 9.3 cm / 560g
↑ 23 × 17 × 13 cm / 840g




65dB

Included
SMC Cable
1 m
056596



OPTIONS

SLM/SPM support
028906



Pb charge Lithium charge OK Error

PRINT



Magnetic mounting

CNT-SPM Smart Printer Module

026919
↓ 14 × 10.5 × 13.3 cm / 1.4 kg
↑ 23 × 17 × 13 cm / 1.9 kg



Customizable receipt

Included
SMC Cable - 1 m
056596



Standard roller x2
57mm x 7.5 m, Ø 25 mm
056633

OPTIONS

SLM/SPM support
028906



USB Keyboard
AZERTY 027725
QWERTY 027770

QWERTY compatibility

BSU SMART COMMUNICATION




CNT-SUM Smart USB Module

025974

USB micro A

↓ 6.9 × 6.8 × 2.9 cm / 85g
↑ 28.5 × 11 × 11.5 cm / 380g

Computer /
Diag System



Included
SMC Cable - 1 m
056596



Computer connection




CNT-SWM Smart Wireless Module

070837

Bluetooth LE Wifi

↓ 6.9 × 6.8 × 2.9 cm / 85g
↑ 27.6 × 9.6 × 9.6 cm / 440g

Computer /
Diag System



Included
SMC Cable - 1 m
056596



SMART HUB MODULE




CNT-SHM Smart Hub Module

025981
↓ 22 × 18 × 4.5 cm / 1 kg
↑ 16.4 × 13.4 × 24 cm / 1.7 kg

Included
SMC Cable
1 m
056596



UP TO 4 MODULES + 4 GYSFLASH



POWER HUB MODULE



CNT-PHM Power Hub Module

056589
↓ 31.7 × 24.5 × 9 cm / 2.7 kg
↑ 32 × 29 × 13.5 cm / 3.2 kg

Included
M6 KIT




4 GYSFLASH IN Ø Cables: 10 → 25 mm²




OUT
Ø Cables: 25 → 70 mm²



SUPPORTS

BSU Flash XL
028890Battery charging rack
Rack de charge
Ladeständer
079595Heavy-duty case
Valise de chantier
Hartschalenkoffer
060432


TROLLEYS

BSU Flash XL
028890BSU Flash Plus
085510robust
tyresOPTION
Protective cover
062733OPTION
Cable support
052284


WALL SUPPORT

Magnetfix 50
029637

✓ for vertical Gysflash

GYSFLASH PRO vertical wall
mounting kit
082694

✓ for vertical Gysflash

Wall support
Tablette
Wandhalterung
055513L 21 x 43 x 57 cm / 3.9 kg
B 36 x 43 x 20 cm / 3.3 kg

✓ for horizontal Gysflash



STANDARD ACCESSORIES

ANDERSON CABLES	for GYSFLASH	
	32.12 PL / 30.12 / 50.12 51.12 / 30.24 / 50.24 / 53.24 25.48 / 51.48 / 53.48	100.12 / 101.12 102.12 / 103.12
Anderson / Clamps		
2.5 m - 10 mm ² 085800	✓	—
2.5 m - 16 mm ² 056503	✓	✓
5 m - 16 mm ² 054615	✓	✓
8 m - 16 mm ² 056572	✓	✓
Anderson / NATO	✓	✓
5 m - 16 mm ² 026810	✓	✓
Anderson / Rema 160 A	✓	✓
5 m - 16 mm ² 069091	✓	✓
Anderson / Anderson 175 A	✓	✓
5 m - 16 mm ² 069107	✓	✓
Anderson / Texas	✓	✓
0.2 m - 16 mm ² 055902	✓	✓
1 m - 16 mm ² 028791	✓	✓

TEXAS CABLES	for GYSFLASH	
	121.12 / 123.12 / 125.12 108.12 / 148.12 / 158.12 101.24 / 103.24 / 107.24	
Texas / Clamps		
2.5 m - 25 mm ² 028876	✓	
5 m - 25 mm ² 027886	✓	
Texas / Rema 160 A	✓	
5 m - 25 mm ² 025714	✓	
Texas / Anderson 175 A	✓	
5 m - 25 mm ² 025721	✓	
Texas / NATO	✓	
5 m - 25 mm ² 025707	✓	
10 m - 25 mm ² 056626	✓	

PARALLEL CABLES KIT 072954	INTERNAL FUSES	EXTERNAL FUSES
Anderson/Cable lugs M6 x2 16 mm ² - 1 m	40 A for GYSFLASH 30 054646 x2	6.3 A for GYSFLASH 30 054578 x5
Cable lugs/Cable lugs M6 x2 (1 red + 1 black) 35 mm ² - 5 m	125 A for GYSFLASH 100, 101, 102 054585 x2	10 A for GYSFLASH 40, 50 100, 101, 102 056527
Texas/Cable lugs M6 x2 25 mm ² 1 m	150 A for GYSFLASH 121, 123, 103 027930 x2	CONNECTORS
M6 KIT Ø16 (x4) Ø25 (x4) Ø35 (x4)		NATO 026780
SMC Cable 1 m		USB key 16 Go/GB 062344

GYSFLASH CNT PACKS

	101.12 CNT 026988	121.12 CNT 026971	CNT-SPM + paper roll + support 026919 + 056633 + 028906	Barcode Scanner + support 027718 + 025745	BSU Flash XL 028890	CNT SLM 027978	CNT SHM 025981	CNT PHM 056589	Parallel cable kit 072954
SINGLE GYSFLASH									
pack GYSFLASH CNT 1 068117	✓	—	✓	✓	✓QWERTY	✓	—	—	—
pack GYSFLASH CNT 2 068124	✓	—	✓	✓	✓AZERTY	✓	—	—	—
pack GYSFLASH CNT 3 068131	—	✓	✓	✓	✓QWERTY	✓	—	—	—
pack GYSFLASH CNT 4 068148	—	✓	✓	✓	✓AZERTY	✓	—	—	—
DOUBLE GYSFLASH									
pack GYSFLASH CNT 5 072978	✓ x2	—	✓	✓	✓AZERTY	✓	✓	✓	✓
pack GYSFLASH CNT 6 074972	✓ x2	—	✓	✓	✓QWERTY	✓	✓	✓	✓
WITHOUT GYSFLASH									
pack Parallel Charging 072961	—	—	—	—	—	—	✓	✓	✓
pack GYSFLASH PRO 1 079908	—	—	✓	✓	✓AZERTY	✓	✓	—	—
pack GYSFLASH PRO 2 079915	—	—	✓	✓	✓QWERTY	✓	✓	—	—



ARTIC

ENERGY

TCB



CHARGERS

IP 65

WATER PROTECTION
ARTIC 1500, 4000 & 8000

CHARGERS ONLY



Save and load settings.
Automatic restart in case of power cut.

Mémorisation des réglages.
Redémarrage automatique en cas de coupure électrique.

Einstellungsspeicherung.
Automatisches Starten nach einem Netzausfall.



Start/stop Engine :
Compatible with Start/Stop vehicles.
Compatible véhicules Start/Stop.
Geeignet für START-STOP-Fahrzeuge.



"Cold charge" mode:
performance-enhancing charging mode for cold or freezing weather conditions.

Mode "Cold charge":
optimisation des performances en cas de temps froid ou de gel.

-Cold Charge--Modus:
Leistungsoptimierung bei kaltem Wetter oder bei Frost.



AUTOMATIC SMART HF INVERTER



ARTIC 800

12V 0.8A GO > 7V



029569

029569



ARTIC 1500

12V 1.5A GO > 7V



029576



ARTIC 4000

6/12V 4/1-4A GO > 2V (6V)
GO > 7V (12V)



029583

029583



ARTIC 8000

2/8A 12V GO > 7V



029590

029590



12V • TRADITIONAL

W

12V • AUTOMATIC

WU

ENERGY 126

4A



023222

023222



TCB 60

2/4A GO > 3.5V



023253

023253



TCB 90

2/5.5A GO > 3.5V



023260

023260



TCB 120

3.5/7A GO > 3.5V



023284

023284



	RECOMMENDATION	5 Ah			10 Ah			15 Ah			20 Ah			40 Ah			80 Ah			90 Ah			110 Ah			120 Ah			180 Ah			240 Ah			300 Ah			+ Ah																																																																																																																																																																																																																																																																																																																																									
		6V	12V	24V																																																																																																																																																																																																																																																																																																																																																																											



CT

CHARGERS



CT 160

9 A

1.5 m - 1.5 mm² → 40 A
024106
025325

CT 210

12 A

1.5 m - 2.5 mm² → 40 A
024113
025349

12/24 V • MANUAL

W

CA

Protection for
on-board electronics

CA 150

10 A

1.5 m - 2.5 mm² → 40 A
024434

CA 360

25 A

2 m - 6 mm² → 60 A
023185

12/24 V • AUTOMATIC

W2

MULTICHARGE



MULTICHARGE CT 48

32 A



026087

12/24/36/48 V • MANUAL

W

WATTMATIC

Protection for
on-board electronics

WATTMATIC 100

5 A



024823

GO > 3.5 V
1.5 m - 1.5 mm² → 40 A

WATTMATIC 170

10 A



025615

GO > 3.5 V
1.8 m - 2.5 mm² → 40 A

6/12 V • AUTOMATIC

WUoU

			CHARGE									
				Average / Moyen (EN 60335)			Efficace / RMS					
				Reg 1	Reg 2	Reg 3						
CT 160	230V, 50 / 60 Hz	190 W	12 / 24 V	12 V > 24 V >	7 A 3 A	9 A (boost) 5 A (boost)	—	13,5 A 7,5 A	2 2	15 A	30.3 × 20.7 × 13.9 / 3.9	3,9 kg
CT 210	230V, 50 / 60 Hz	260 W		12 / 24 V	12 V > 24 V >	8 A 4 A	12 A (boost) 6 A (boost)	—	18 A 9 A			
MULTICHARGE CT 48	230V, 50 / 60 Hz	1200 W	12 / 24 / 36 / 48 V		12 V > 24 V > 36 V > 48 V >	20,8 A > 32,4 A 20,1 A > 31,8 A			31 A 29 A	6 6	40 A	40.5 × 34 × 24 / 15.8
				19,6 A > 22,4 A (30,4 A boost)			29 A	6				
				15,5 A > 18,7 A (24,3 A boost)			28 A	6				
CA 150	230V, 50 / 60 Hz	500 W	12 / 24 V		8 A	10 A (boost)	—	18 A	2	25 A	32.8 × 25.5 × 14.6 / 6.5	6 kg
CA 360	230V, 50 / 60 Hz	920 W	12 / 24 V		7 A	15 A (boost1)	25 A (boost2)	37 A	3	50 A	43 × 30 × 23 / 14	14 kg
WATTMATIC 100	230V, 50 Hz	170 W	6 / 12 V		3 A	5 A		11.4 A	2	10 A	26.9 × 24.3 × 12.8 / 3.7	3.8 kg
WATTMATIC 170	230V, 50 Hz	280 W	6 / 12 V		6.5 A	10 A (boost)	—	18.8 A	2	20 A	33.9 × 22.2 × 13.6 / 5	5 kg

RECOMMENDATION	5 Ah			10 Ah	15 Ah	20 Ah	40 Ah			80 Ah	90 Ah	110 Ah	120 Ah			180 Ah			240 Ah	300 Ah	+ Ah							
	6V	12V	24V																									
CT 160		•	•						12 V : 25 , 160 Ah - 24 V : 15 > 90 Ah																			
CT 210		•	•						12 V : 35 , 210 Ah - 24 V : 20 > 100 Ah																			
MULTICHARGE CT 48		•	•	+48 V									12, 24, 36 V : 90 , 450 Ah - 48 V : 70 , 360 Ah															
CA 150		•	•						35 , 150 Ah																			
CA 360		•	•						40 , 350 Ah																			
WATTMATIC 100	•	•							15 , 100 Ah																			
WATTMATIC 170	•	•							25 , 180 Ah																			



STARTUP

CHARGERS & STARTERS

AUTOMATIC

W2

SSM SELF START MEMORY



3 in 1

CHARGE

+

TEST

+

START

START / NEOSTART

CHARGERS & STARTERS

TRADITIONAL

W

SSM SELF START MEMORY



Fuse x2

50 A
Start 200
054622

80 A
Start 300
054653

150 A
Neostart 320
054639

200 A
Neostart 420, 620
054547



CHARGERS & STARTERS

12 - 24 V

TRADITIONAL

START	48
NEOSTART	49

AUTOMATIC

STARTIUM	50
----------	----

BATTERY SUPPORT UNIT

DIAG-STARTIUM	51
---------------	----

12 V

STARTUP 80

17 A

SSM

1.5 m - 2.5 mm² ➔ 30 A

024922

🇪🇺 : 025127

12V | 12/24 V

START 200

18 A

SSM

1.5 m - 6 mm² ➔ 60 A

025530

START 300

23 A

SSM

2 m - 10 mm² ➔ 220 A

025547

NEOSTART 320

9 / 40 A

SSM

2 m - 10 mm² ➔ 220 A

025301

12/24 V

NEOSTART 420

40 A

SSM

1.8 m - 10 mm² ➔ 500 A

025295

NEOSTART 620

60 A

SSM

1.8 m - 16 mm² ➔ 500 A

025288

🇪🇺 : 025486

DESIGN GYS FRANCE MADE IN GYS CHINA		I ₁				CHARGE									START			
				CHARGE kW	START kW		RMS / Efficace	Average / Moyen (EN 60335)	Boost	Automatic	Manual		min > max	1V/C	0V/C	Fuse	LxWxH cm / kg	LxWxH cm / kg
START UP 80	230V	13 A	12V	0,35	1	2	13,-25 A	9 A	17 A	•	—	40 > 170 Ah	50 A	80 A	—	17 x 11.5 x 31 / 4	19 x 12 x 32 / 4.2	
START 200	230V	13 A	12V	0,39	1,4	3	15-25 A	11 A	18 A	—	•	53 > 240 Ah	80 A	120 A	50 A	35 x 24 x 15 / 7.6	37 x 27 x 18 / 8	
START 300	230V	13 A	12V	0,8	3,6	3	13-36 A	10 A	23 A	—	•	42 > 300 Ah 38 > 224 Ah	100 A	165 A	80 A	36 x 27 x 20 / 12.4	40 x 35 x 23.5 / 13.7	
		13 A	24V	1,2	3,6			8 A	17 A				160 A	270 A	150 A	41 x 30 x 21 / 13	41 x 35 x 24 / 14.7	
NEOSTART 320	230V	13 A	12/ 24V	0,8	6,5	3	40 A	10 A 9 A	40 A 30 A	—	•	20 > 700 Ah	160 A	270 A	150 A	41 x 30 x 21 / 13	41 x 35 x 24 / 14.7	
NEOSTART 420	230V	16 A	12/ 24V	1,7	9	3	70 A	20 A	40 A	—	•	20 > 1000 Ah	250 A	420 A	200 A	48 x 30 x 23 / 18	52 x 34 x 31 / 21	
NEOSTART 620	230V	16 A	12/ 24V	2	10	3	90 A	30 A	60 A	—	•	20 > 1350 Ah	330 A	620 A	200 A	31.5 x 23 x 44.5 / 23.7	21 x 33.5 x 26.5 / 24	

i Recommendation	5 Ah		10 Ah		15 Ah		20 Ah		40 Ah		80 Ah		90 Ah		110 Ah		120 Ah		180 Ah		240 Ah	
	6V	12V	24V																			
START UP 80		•								35 > 50 Ah												
START 200		•							35 > 40 Ah	40 > 80 Ah												
START 300		•	•						35 > 50 Ah	50 > 100 Ah												
NEOSTART 320		•	•								35 > 60 Ah	60 > 120 Ah										
NEOSTART 420		•	•									35 > 80 Ah	80 > 160 Ah									
NEOSTART 620		•	•										45 > 100 Ah	100 > 200 Ah								

CHARGERS & STARTERS

AUTOMATIC



3 in 1

 **AUTOMATIC CHARGE**
= BATTUM

 **AUTOMATIC START**

 **TEST ALTERNATOR**

 **TIMER**

 **UNIVERSAL MODE**

 **SULFATED BATTERIES**

 **ALL BATTERIES**

 **>1V**

 **FULL PROTECTION**

 On-board electronics

 Over voltage

 No sparks





35/50 mm²

CHARGERS & STARTERS

AUTOMATIC & BSU

BATTERY SUPPORT UNIT

BSU Battery Support Unit

POWER SUPPLY
DIAG+ 60A
Voltage adjustable 12 V • 15 V

 **BATTERY EXPERT**





 **Compatibility**
p.63

12/24 V


12V

6/12/24 V

STARTIUM 330E
25 A
1,9 m - 10 mm² ➔ 500 A
026469

STARTIUM 480E
40 A
1,9 m - 16 mm² ➔ 600 A
026483
 : 025578

STARTIUM 680E
45 A
2,2 m - 25 mm² ➔ 600 A
026490
 : 025585


STARTIUM 980E
50 A
2,5 m - 35 mm² ➔ 600 A
026506
 Disconnectable

DIAG STARTIUM 60-12
60 A
2,2 m - 25 mm² ➔ 600 A
026513

DIAG STARTIUM 60-24
60 A
2,2 m - 25 mm² ➔ 600 A
026520
 : 025592
 : 076969

MADE IN FRANCE		I ₁		CHARGE 							START 			BSU				CCA I (EN) START	
	CHARGE kW			START kW		min › max	RMS / Efficace	Average / Moyen (EN 60335)		Boost	Automatic	1V/Cell	0V/Cell						AUTO START
STARTIUM 330E	230V	16 A	0,8	6,5	12V 24V	20 › 370 Ah 20 › 300 Ah	40 A	25 A	4	—	●	12V : 24V : 165 A 130 A 270 A 210 A	●	—	100 A	26 x 26 x 47 / 15.5	28 x 28 x 47 / 16	500 A	
STARTIUM 480E	230V	16 A	1,7	9	12V 24V	20 › 600 Ah 20 › 450 Ah	65 A	30 A	4	40 A	●	12V : 24V : 280 A 210 A 390 A 290 A	●	—	200 A	34 x 30 x 64 / 20.5	64 x 37 x 31 / 29	750 A	
STARTIUM 680E	230V	16 A	2	10	12V 24V	20 › 675 Ah 20 › 525 Ah	75 A	30 A	4	45 A	●	12V : 24V : 380 A 270 A 550 A 380 A	●	—	200 A	34 x 30 x 64 / 25.5	65 x 37 x 31 / 31	900 A	
STARTIUM 980E	230V	16 A	2	12	12V 24V	20 › 750 Ah 20 › 525 Ah	80 A	40 A	4	50 A	●	12V : 24V : 500 A 400 A 720 A 560 A	●	—	250 A	34 x 30 x 80 / 30	65 x 37 x 32 / 36	1400 A	
DIAG STARTIUM 60-12	230V	16 A	2	10	12V	20 › 900 Ah	95 A	60 A	4	—	●	12V : 310 A 440 A	●	●	200 A	35 x 35 x 72 / 30.5	80 x 37 x 35 / 36	900 A	
DIAG STARTIUM 60-24	230V	16 A	2	10	6V	20 › 900 Ah	65 A	40 A	4	—	—	6V : —	●	●	200 A	35 x 35 x 72 / 30.5	80 x 37 x 35 / 36	900 A	
					12V	20 › 900 Ah	95 A	60 A				12V : 300 A 430 A							
					24V	20 › 525 Ah	65 A	40 A				24V : 280 A 410 A							

 **Fuse x2**
100 A
Startium 330E
054394
200 A
Startium 480E, 680E,
Diag. 60-12, 60-24
054547
250 A
Startium 980E
055568



BOOSTERS
Pb/LEAD INSIDE



12 V 28 Ah INSIDE
HOBBIES OCCASIONAL PRO INTENSIVE



INCLUDED GYSPACK 660

CHARGER
Power in 100-240 V/out 12 V
50/60 Hz
027992 025929

REGULATED IVOU FAST CHARGE

FV FLEXIBLE VOLTAGE
100V 240V



DESIGN GYS FRANCE

MADE IN
GYS CHINA

MADE IN
FRANCE

56

FOR GYSPACK 660/750/800/700/900

Fuse x2 200 A 054547 300 A 054561



OPTION

MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202



Fuse 7,5 A



SPIRAL TECHNOLOGY



12 V 28 Ah SPIRAL INSIDE
HOBBIES OCCASIONAL PRO INTENSIVE



INCLUDED GYSPACK 750

CHARGER
Power in 100-240 V/out 12 V
50/60 Hz
054684 054691

REGULATED IVOU FAST CHARGE

FV FLEXIBLE VOLTAGE
100V 240V



SPIRAL TECHNOLOGY



12 V 28 Ah SPIRAL INSIDE
HOBBIES OCCASIONAL PRO INTENSIVE



INCLUDED GYSPACK PRO 800

CHARGER
Power in 100-240 V/out 12 V
50/60 Hz
054684 054691

REGULATED IVOU FAST CHARGE

FV FLEXIBLE VOLTAGE
100V 240V




PREMIUM QUALITY BATTERIES

TPPL TECHNOLOGY
Thin Plate
Pure Lead




12 V 16 Ah INSIDE
HOBBIES OCCASIONAL PRO INTENSIVE



INTEGRATED CHARGER
7 STEP

12 V 30 Ah INSIDE
HOBBIES OCCASIONAL PRO INTENSIVE



INTEGRATED CHARGER
7 STEP

RECOMMENDATION	5 Ah			10 Ah		15 Ah		20 Ah		40 Ah		80 Ah		90 Ah		110 Ah		120 Ah			180 Ah			240 Ah		300 Ah		+ Ah	
	6V	12V	24V																										
GYSPACK 660																													
GYSPACK 750																													
GYSPACK PRO 800																													
GYSPACK PRO 700																													
GYSPACK PRO 900																													

STARTPACK

BOOSTERS

Pb/LEAD

INSIDE

+

POWER SUPPLY
12V DC



YouTube

PLAYLIST
STARTPACK

12/24 V

22Ah + 22Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

STARTPACK TRUCK

12V	3 200 A	750 A 1V/Cell
24V	1 600 A	650 A 1V/Cell

1.8 m - 25 mm² ➤ 600 A 025448
🇬🇧 : 026339

STARTPACK TRUCK MOBILE

12V	3 200 A	750 A 1V/Cell
24V	1 600 A	650 A 1V/Cell

1.8 m - 25 mm² ➤ 600 A 026025
🇬🇧 : 028807

INCLUDED STARTPACK TRUCK & TRUCK MOBILE

CHARGER

⊕ Power in 100-240 V/out 12 V
50/60 Hz
054684
🇬🇧 : 054691

REGULATED

100V

FAST CHARGE

FV

FLEXIBLE VOLTAGE

100V

240V

OPTION

MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202

Fuse 7,5 A



DESIGN GYS FRANCE						START PETROL & DIESEL			INSIDE						LxWxH cm	LxWxH cm / kg	
		2 × 22 Ah	12V	750 A	1450 A	3200 A	Pb/Lithium LFP		50 / 60 Hz	230V	12V/2 A DC				1 × 300 A	37 x 20 x 46	39 x 22 x 50 / 18
MADE IN GYS CHINA	STARTPACK TRUCK	2 × 22 Ah	12V	750 A	1450 A	3200 A	Pb/Lithium LFP		110 - 240 V	—	12V/2 A DC				1 × 300 A	37 x 20 x 46	39 x 22 x 50 / 18
	/ TRUCK MOBILE		24V	650 A	1300 A	1600 A	Pb/Lithium LFP										
MADE IN FRANCE	STARTPACK 12.24 CI	2x 16 Ah	12V	900 A	1700 A	3600 A	Pb/Lithium LFP	—	220 - 240 V	4 A	—			—	1 × 300 A	26 x 20 x 48	34 x 20 x 51 / 19
			24V	700 A	1350 A	1800 A	Pb/Lithium LFP										
	STARTPACK PRO 12.24 CI	2x 30 Ah	12V	1300 A	2400 A	6200 A	Pb/Lithium LFP	—	220 - 240 V	4 A	—			—	1 × 300 A	14 x 35 x 56	63 x 39 x 30 / 34
			24V	1200 A	2250 A	3100 A	Pb/Lithium LFP										

YouTube

PLAYLIST
STARTPACK

12/24 V

16Ah + 16Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

STARTPACK 12.24 CI

12V	3600 A	900 A 1V/Cell	24V ★	1 800 A	700 A 1V/Cell
-----	--------	------------------	-------	---------	------------------

1.8 m - 35 mm² ➤ 600 A 024991
🇬🇧 : 068155

STARTPACK PRO 12.24 CI

12V	6200 A	1300 A 1V/Cell	24V ★★★	3100 A	1200 A 1V/Cell
-----	--------	-------------------	---------	--------	-------------------

2 m - 50 mm² ➤ 600 A 028920
🇬🇧 : 068162

12/24 V

30Ah + 30Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

STARTPACK 12.24 CI

12V	3600 A	900 A 1V/Cell	24V ★	1 800 A	700 A 1V/Cell
-----	--------	------------------	-------	---------	------------------

1.8 m - 35 mm² ➤ 600 A 024991
🇬🇧 : 068155

STARTPACK PRO 12.24 CI

12V	6200 A	1300 A 1V/Cell	24V ★★★	3100 A	1200 A 1V/Cell
-----	--------	-------------------	---------	--------	-------------------

2 m - 50 mm² ➤ 600 A 028920
🇬🇧 : 068162

INCLUDED STARTPACK 12.24 & PRO 12.24

Fuse x2

200 A 054547

300 A 054561

INTEGRATED CHARGER

7 STEP

After each use
Après chaque utilisation
Nach jeder Anwendung

RECOMMENDATION	6V		12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
	6V	12V	24V	6V	6V	6V	6V	6V	6V	6V	6V	6V	6V	6V	6V	6V	6V
STARTPACK TRUCK		•	•														
STARTPACK TRUCK MOBILE		•	•														
STARTPACK 12.24 CI		•	•														
STARTPACK PRO 12.24 CI		•	•														



SELECT THE RIGHT BOOSTER
CHOISISSEZ VOTRE BOOSTER • WÄHLEN SIE IHREN BOOSTER AUS

6/12 V		12 V										12-24 V				
GYSPACK HERITAGE		GYSPACK AIR 401	GYSPACK AIR	GYSPACK 400	GYSPACK 600	GYSPACK PRO	GYSPACK 660	GYSPACK PRO 700	GYSPACK 750	GYSPACK PRO 800	GYSPACK PRO 900	STARTPACK TRUCK/ TRUCK MOBILE	STARTPACK 12.24 CI	STARTPACK PRO 12.24 CI	STARTPACK PRO 12.24 XL	ENERGY STATION FP
025844		088801	026322	025455	027336	026155	027862	027077	026179	068759	027084	025448/ 026025	024991	028920	026711	069589
6 V		12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V
12 V		12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	24V	24V	24V	24V	24V
START	1V/Cell	400 (6 V)	380 A	480 A	480 A	550 A	600 A	640 A	640 A	750 A	700 A	750 (12 V)	900 A (12 V)	1300 A (12 V)	1600 A (12 V)	/
	450 (12 V)											650 (24 V)	700 A (24 V)	1200 A (24 V)	1400 A (24 V)	
	800 (6 V)											1450 A (12 V)	1700 A (12 V)	2400 A (12 V)	3000 A (12 V)	
	0V/Cell	850 (12 V)	700 A	900 A	900 A	1050 A	1100 A	1200 A	1200 A	1450 A	1320 A	1300 A (24 V)	1350 A (24 V)	2250 A (24 V)	2600 A (24 V)	
	850 (12 V)											3200 A (12 V)	3600 A (12 V)	6200 A (12 V)	8500 A (12 V)	
PEAK BATTERY	3200 (6 V)	1100 A	1250 A	1250 A	1750 A	1750 A	1900 A	1800 A	2500 A	2500 A	3100 A	1600 A (24 V)	1800 A (24 V)	3100 A (24 V)	4250 A (24 V)	
	1600 (12 V)															
2 × 20 Ah		17 Ah	18 Ah	18 Ah	22 Ah	22 Ah	28 Ah	16 Ah	28 Ah	28 Ah	30 Ah	2 × 22 Ah	2 × 16 Ah	2 × 30 Ah	2 × 50 Ah	
								EnerSys			EnerSys	EnerSys	EnerSys	EnerSys	EXIDE TECHNOLOGIES	
SPIRAL TECHNOLOGY																
ON OFF		■	■	■		■	■	■	■	■	■	■	■	■	■ automatic	■
TEST OK		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
external 2 A		external 1 A	external 0,5 A	external 0,5 A	external 0,5 A	external 0,5 A	external 2 A	internal 2,5 A	external 2 A	external 2 A	internal 2,5 A	external 2 A	internal 4 A	internal 4 A	external 6 A	internal 30A
IUoU		WU	WU	WU	WU	WU	IUoU	7 step	IUoU	IUoU	7 step	IUoU	7 step	7 step	7 step	6 step
12 V DC		12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC				
		■	■													
		■	■			■	■					■				
1,8 m ø25 mm²		1,2 m ø12,5 mm²	1,1 m ø25 mm²	0,6 m ø16 mm²	0,6 m ø16 mm²	1,1 m ø25 mm²	1,3 m ø25 mm²	1,4 m ø25 mm²	1,3 m ø25 mm²	1,8 m ø25 mm²	1,8 m ø35 mm²	1,8 m ø25 mm²	1,8 m ø35 mm²	2 m ø50 mm²	2 m ø70 mm²	2,5 m ø50 mm²
37×20×46		31×19×32	33×17×37	26×10×29	26×10×29	35×14×37	35×19×40	33×15×32	35×19×40	31×19×35	33×15×32	37×20×46/ 37×20×57	34×18×46	63×39×30	112×35×43	70×65×91
18 kg		7,4 kg	8,5 kg	6,5 kg	6,5 kg	9 kg	13,5 kg	12 kg	13,5 kg	18,4 kg	16 kg	18/21 kg	22 kg	34 kg	68 kg	29 kg +

After each use
Après chaque utilisation
Nach jeder Anwendung

CAUTION ON STAND BY
Keep your GYSPACK connected to the
mains supply.

ATTENTION HORS UTILISATION
Laisser en charge en permanence.

ACHTUNG WENN NICHT IN GEBRAUCH
Ladegerät dauernd angeschlossen lassen.

ATTENTION CUANDO ESTA APAGADO
Dejar el cargador conectado permanentemente.

ATTENZIONE FUORI USO
Lasciare sempre in carica.

★

★★★★

★★★★★

MINI PRO PRO UNIVERSAL PRO



NATO / OTAN : COMPATIBLE PRODUCTS
- Produits compatibles - Kompatible Produkte



	GYSLASH 30.12, 50.12 FV, 51.12, 100.12, 101.12 CNT	GYSLASH 101.24 CNT FV 121.12 CNT FV 125.12 CNT FV 157.12 CNT FV	GYSLASH 123.12 CNT FV 103.24 CNT FV 107.24 CNT FV	GYSLASH 108.12 CNT FV 148.12 CNT FV 158.12 CNT FV	GYSLASH 53.48 CNT FV	GYSLASH 15.24 XTREM	STARTIUM 980E	STARTPACK PRO 12.24 XL
NATO CONNECTOR 026780								
Anderson/NATO 5 m - 16 mm² 026810	✓	—	—	—	✓	—	—	—
Texas/NATO 5 m - 25 mm² 025707	—	✓	✓	✓	—	—	—	—
10 m - 25 mm² 056626	—	—	—	—	—	—	—	—
Texas/NATO 3.5 m - 50 mm² 025653	—	—	—	—	—	—	✓	—
Anderson/NATO 2 m - 50 mm² 026803	—	—	—	—	—	—	—	✓
3 m - 50 mm² 072589	—	—	—	—	—	—	—	—
2pts/NATO 5 m - 4 mm² 025837	—	—	—	—	—	✓	—	—
2pts/NATO Spiral 5 m 028968	—	—	—	—	—	✓	—	—





TRACTION BATTERIES : COMPATIBLE PRODUCTS
- Produits compatibles - Kompatible Produkte

BATIUM 25/24 X

GYSLASH 30.24, 50.24 & 101.24

GYSLASH 103.24 & 53.48



		TYPE	6 h	7 h	8 h	9 h	10 h	11 h	12 h	13 h	14 h	CURRENT
24 V	BATIUM 25.24 X	liquid	75 Ah	90 Ah	120 Ah	125 Ah	130 Ah	140 Ah	155 Ah	165 Ah	180 Ah	25 A
	GYSFLASH 30.24 HF	liquid	—	—	—	75 Ah	85 Ah	105 Ah	125 Ah	145 Ah	175 Ah	15 A
		gel	—	—	—	—	—	75 Ah	85 Ah	105 Ah	120 Ah	
	GYSFLASH 50.24 HF	liquid	—	—	—	250 Ah	290 Ah	350 Ah	410 Ah	480 Ah	550 Ah	50 A
		gel	—	—	—	—	—	260 Ah	290 Ah	340 Ah	400 Ah	
	GYSFLASH 51.12	liquid	130 Ah	150 Ah	180 Ah	210 Ah	240 Ah	270 Ah	310 Ah	350 Ah	390 Ah	25 A
		gel	—	—	130 Ah	150 Ah	160 Ah	180 Ah	200 Ah	220 Ah	240 Ah	
	GYSFLASH 101.24	liquid	390 Ah	470 Ah	550 Ah	630 Ah	720 Ah	820 Ah	930 Ah	1050 Ah	1200 Ah	100 A
		gel	—	—	400 Ah	450 Ah	500 Ah	560 Ah	610 Ah	670 Ah	720 Ah	
	GYSFLASH 103.24	liquid	490 Ah	580 Ah	680 Ah	790 Ah	900 Ah	1020 Ah	1160 Ah	1310 Ah	1500 Ah	100 A
		GYSFLASH 107.24	gel	—	—	500 Ah	560 Ah	630 Ah	700 Ah	760 Ah	830 Ah	
	36 / 48 V	GYSFLASH 25.48	liquid	130 Ah	150 Ah	180 Ah	210 Ah	240 Ah	270 Ah	310 Ah	350 Ah	390 Ah
gel			—	—	130 Ah	150 Ah	160 Ah	180 Ah	200 Ah	220 Ah	240 Ah	
GYSFLASH 51.48 GYSFLASH 53.48		liquid	260 Ah	310 Ah	360 Ah	420 Ah	480 Ah	540 Ah	610 Ah	690 Ah	790 Ah	50 A
		gel	—	—	260 Ah	300 Ah	330 Ah	370 Ah	400 Ah	440 Ah	470 Ah	

100 A		Cables Anderson 175A/Texas
	5 m - 25 mm²	025721
100 A		Cables REMA 160A/Texas
	5 m - 25 mm²	025714
15 A		Cables REMA 160A/Anderson
	5 m - 16 mm²	069091
50 A		Cables Anderson 175A/Anderson
	5 m - 16 mm²	069107

BOOSTERS

LITHIUM

INSIDE

 SPECIALIST HOBBY • Non professional use • Utilisation non professionnelle • Nicht für gewerblichen Gebrauch.

-  START ENGINE
-  POWER BANK
- 
-  LIGHT

INCLUDED

 SUPER-SAFE SMART STARTING CABLE







12V

NOMAD POWER 401

900 A

350 A

1V/Cell



0,28 m - 5,2 mm²
AWG10
 SUPER-SAFE
SMART STARTING
CABLE

087316

NOMAD POWER 501

1200 A

500 A

1V/Cell



0,28 m - 5,2 mm²
AWG10
 SUPER-SAFE
SMART STARTING
CABLE

087323

	 LITHIUM			 START			 START PETROL & DIESEL	 INPUT	 OUTPUT	 cm	 kg
	CAPACITY/CELL	TYPE	FULL CHARGE	1V/Cell	0V/Cell	Peak Battery					
NP 401	2.5 Ah - 37 Wh	LiCoO2	3 h	350 A	700 A	900 A	12 V (Pb only)	USB-C : 5V/2A	(×1) USB 3.0 QC : 5/9/12V - 2A (×1) USB-A : 5V - 2.1A	14.5 × 8.5 × 3	0.37
NP 501	3 Ah - 45 Wh	LiCoO2	3 h 30	500 A	1000 A	1200 A	12 V (Pb only)	USB-C : 5V/2A	(×1) USB 3.0 QC : 5/9/12V - 2A (×1) USB-A : 5V - 2.1A (×1) JACK DC ø5.5 : 15V - 5A	17.5 × 8.5 × 3	0.46
NP PRO 701	4 Ah - 59.2 Wh	LiCoO2	3 h	700 A	1100 A	1250 A	12 V (Pb only)	USB-C : 5V/3A	(×1) USB 3.0 QC : 5V/2.4A 9V/2A 12V - 1.5A (×1) USB-A : 5V - 2.1A (×1) USB-C : 5V - 3A (×1) JACK DC ø5.5 : 15V - 10A	22.8 × 10 × 3.8	0.62
NP PRO 801	5 Ah - 74 Wh	LiCoO2	4 h	850 A	1300 A	1500 A	12 V (Pb only)	USB-C : 5V/3A	(×1) USB 3.0 QC : 5V/2.4A 9V/2A 12V - 1.5A (×1) USB-A : 5V - 2.1A (×1) USB-C : 5V - 3A (×1) JACK DC ø5.5 : 15V - 10A	22.8 × 10 × 3.8	0.73
NP PRO 901 FC	6 Ah - 92.5 Wh	LiCoO2	5h (with 15W charger) 1h15 (with 67W charger)	900 A	1400 A	1700 A	12 V (Pb only)	PD USB-C : 60W max	(×1) USB 3.0 QC : 5V/2.4A 9V/2A 12V - 1.5A (×1) USB-A : 5V - 2.1A (×1) USB-C Power Delivery : 60W (×1) JACK DC ø5.5 : 15V - 10A	22.8 × 10 × 3.8	0.79



Normal charge 100% in 3 h

Normal charge 100% in 4 h

FAST CHARGE
100% in 1 h 15

12 V

NOMAD POWER PRO 701

1250 A

700 A

1V/Cell



0,26 m - 8,3 mm²
AWG8
 SUPER-SAFE
SMART STARTING
CABLE

085855

NOMAD POWER PRO 801

1500 A

850 A

1V/Cell



0,26 m - 8,3 mm²
AWG8
 SUPER-SAFE
SMART STARTING
CABLE

085831

NOMAD POWER PRO 901 FC

1700 A

900 A

1V/Cell



0,26 m - 8,3 mm²
AWG8
 SUPER-SAFE
SMART STARTING
CABLE

085879

Recommendation 												
	5 > 70 Ah											
NP 401												
NP 501												
NP PRO 701												
NP PRO 801												
NP PRO 901 FC												

OPTION



67 W Fast USB-C Charger
✓ Nomad Power PRO 901 FC
087132



15 W USB-C Charger
✓ Nomad Power 401 / 501
✓ Nomad Power PRO 701 / PRO 801 / PRO 901 FC
087101



15 W USB-C Charger
✓ Nomad Power 401 / 501
✓ Nomad Power PRO 701 / PRO 801 / PRO 901 FC
087354

NOMAD POWER

BOOSTERS

LITHIUM

INSIDE

SPECIALIST HOBBY • Non professional use • Utilisation non professionnelle • Nicht für gewerblichen Gebrauch.

3 Lights modes
Normal
Flashing
S.O.S

NEW
12 2025

3 Lights modes
Normal
Flashing
S.O.S

NEW
12 2025

12 V

NOMAD POWER PRO XL

2000 A

1000 A
1V/Cell

0,7 m - 21 mm²
AWG4

USB-C / USB-C

088818

NOMAD POWER PRO XXL

3200 A

1500 A
1V/Cell

0,6 m - 21 mm²
AWG4

088924

OPTION

67 W Fast USB-C Charger
✓ Nomad Power PRO 901 FC
087132

15 W USB-C Charger
✓ Nomad Power 401 / 501
✓ Nomad Power PRO 701
/ PRO 801 / PRO 901 FC
087101

15 W USB-C Charger
✓ Nomad Power 401 / 501
✓ Nomad Power PRO 701
/ PRO 801 / PRO 901 FC
087354

3 Lights modes
Normal
Flashing
S.O.S

218 Wh

NEW
11 2025

NOMAD POWER
12/24 V
088931

3 Lights modes
Normal
Flashing
S.O.S

Ultra High Capacity
499+ Wh

NEW

NOMAD
POWER
PRO 12/24 V
088566

Maximum
autonomy

× 2
Increased
vehicle starts

12 / 24 V

NOMAD POWER PRO TRUCK

2000 A

600 A
1V/Cell

0,55 m - 13,3 mm²
AWG6

027527
028845

NOMAD POWER 12/24 V

4000 A

2300 A
1V/Cell

0,7 m - 21 mm²
AWG4

088931

NOMAD POWER PRO 12/24 V

5000 A

2300 A
1V/Cell

0,7 m - 21 mm²
AWG4

088566

MADE IN CHINA	LITHIUM			START			START PETROL & DIESEL	INPUT	OUTPUT		POWER BANK		cm	kg
	CAPACITY/CELL	TYPE	FULL CHARGE	1 V/Cell	0 V/Cell	Peak Battery					OBD supply compatibility (with 054202)			
NP PRO XL	8 Ah - 118.4 Wh	LiPo	2 h with 67 W Fast USB-C charger 6.5 h with 15 W USB-C charger	1000 A	1500 A	2000 A	12 V (Pb/Lead only)	—	(×1) USB-C : 60 W max (×1) USB-A : 5 V - 2.4 A	(×1) USB 3.0 Quick charge : 5/9/12 V (×1) DC : 12/16 V - 10 A	—		31.1 × 15.2 × 6,5	2.2
NP PRO XXL	10.4 Ah - 153.9 Wh	LiCoO2	3 h	1500 A	2500 A	3200 A	12 V (Pb/Lead only)	(×1) USB-C : 5/9 V - 2 A/ 9 V - 2 A JACK DC 16.8 V/4 A	(×1) USB-A : 5 V - 2.4 A (×1) USB-A : 5 V - 1 A		—		25.2 × 15 × 18.8	3.1
NP PRO TRUCK	6 Ah - 155.4 Wh	LiCoO2	7 h	600 A	1500 A	2000 A	12 V/24 V (Pb/Lead only)	QC USB-C : 18 W max	(×1) USB-A : 5 V - 1 A (×1) USB-A : 5 V - 2.1 A	(×1) Cigarette Lighter : 12 V - 10 A	•		24.8 × 24.8 × 9.6	2.4
NP 12/24V	8.4 Ah - 218 Wh	LiCoO2	4 h	1900 A	3000 A	4000 A	12 V/24 V (Pb/Lead only)	(×1) USB-C : 5 V - 2 A/ 9 V - 2 A JACK DC 29 V/5 A	(×2) USB-A : 5 V - 2.4 A		•		29.5 × 24.5 × 17.5	4.4
NP PRO 12/24V	19.5 Ah - 499.59 Wh	LiCoO2	7 h	2300 A	3500 A	5000 A	12 V/24 V (Pb/Lead only)	JACK DC ø5.5: 29 V - 5 A USB-C: 5V/2A 9 V/2 A	(×2) USB-A : 5 V - 2.4 A		•		24.6 × 24.5 × 15	5.4

Recommendation																
NP PRO XL	5 > 180 Ah															
NP PRO XXL	5 > 180 Ah															
NP PRO TRUCK	5 > 140 Ah															
NP 12/24V	5 > 180 Ah															
	> 240 Ah															
NP PRO 12/24V	5 > 180 Ah															
	> 240 Ah															

67

NOMAD POWER

LITHIUM INSIDE



BOOSTERS SUPER CAPACITOR

INSIDE


SUPER CAPACITOR TECHNOLOGY FOR STARTRONIC & GYSCAP



- ✓ NO BATTERY INSIDE
- ✓ NO MAINTENANCE
- ✓ FAST TO USE

- ✓ BOOSTER SANS BATTERIE INTERNE
- ✓ AUCUNE MAINTENANCE
- ✓ RAPIDE D'UTILISATION


- ✓ KEINE INTERNE BATTERIE
- ✓ KEINE WARTUNG
- ✓ SCHNELL EINSETZBAR




FULL
PROTECTION



-40/+65°C




1 MILLION
CYCLES



FAST
CHARGE



NO SULFATION
DURING
STORAGE



UNLIMITED
STARTS

CHARGING MODES

	Vehicle battery	Cigarette lighter	Internal lithium battery
STARTRONIC 800	✓	✓	—
STARTRONIC HYBRID 900	✓	✓	✓
STARTRONIC SUPERCAP 12/24 V	✓	—	—

DC/DC CONVERTER INSIDE (>5V)



800 : 4 minutes
HYBRID 950 : 4 minutes
SUPERCAP 12 / 24 V : 5 minutes



INCLUDED
STARTRONIC 800
& HYBRID 950
CIGARETTE LIGHTER
for Easy charge
027404
12 V



- ✓ SMART
- ✓ SAFE
- ✓ POWERFUL



- ➕ Output USB
- ➕ Light

INCLUDED
Internal lithium battery
027411



100 % → Recharge the
supercapacitors 5 times

5×
800
F

INSIDE

12 V

STARTRONIC 800

800 A

12 V

DC/DC
converter

026735



5×
950
F

INSIDE

+ Lithium

STARTRONIC HYBRID 950

950 A

12 V

DC/DC
converter

026117



12 V / 24 V

STARTRONIC SUPERCAP 12 / 24V

1050 A

12 V

DC/DC
converter

880 A

24 V

082816



10×
900
F

INSIDE

MADE IN CHINA							⏻ INPUT CHARGE				⌚ Charging time							
	START 		 START PETROL & DIESEL		Number of Capacitors	Integrated Inverter	 12 V		 12 V/10 A				 5 V/2 A		 internal lithium battery	 LIGHT	 cm	 kg
	1 V/Cell	0 V/Cell Peak					OFF	ON	OFF	ON			MICRO USB Type B					
STARTRONIC 800	800 A	1 400 A	—	Pb only	12 V	5 × 800 F	●	4 min	60 s	4 min	4 min		5 V/2 A	40 min	—	—	26,7 × 19,5 × 5	1,86
STARTRONIC HYBRID 950	950 A	1 660 A	—	Pb only	12 V	5 × 950 F	●	4 min	60 s	4 min	4 min		5 V/2 A	40 min	30 min	●	25 × 18,5 × 6	1,86
STARTRONIC SUPERCAP 12/24V	1 050 A	1 800 A	—	Pb only	12 V	10 × 900 F	●	5 min	3 min	—	—		—	—	—	—	34 × 43 × 20	7
	880 A	1500 A			24 V			2 min	2 min									



Recommendation

STARTRONIC 800

5 × 90 Ah

STARTRONIC HYBRID 950

5 × 100 Ah


STARTRONIC SUPERCAP 12/24V

5 × 150 Ah

STARTRONIC 800										
STARTRONIC HYBRID 950										
STARTRONIC SUPERCAP 12/24V										



GYSCAP



SMART STARTER MANAGEMENT SYSTEM

SUPER CAPACITOR TECHNOLOGY

FULL PROTECTION -40/+65°C

✓ NO BATTERY INSIDE
✓ NO MAINTENANCE
✓ FAST TO USE

✓ BOOSTER SANS BATTERIE INTERNE
✓ AUCUNE MAINTENANCE
✓ RAPIDE D'UTILISATION

✓ KEINE INTERNE BATTERIE
✓ KEINE WARTUNG
✓ SCHNELL EINSETZBAR

1 MILLION CYCLES

FAST CHARGE

NO SULFATION DURING STORAGE

UNLIMITED STARTS

NEW 03/2026



12 V

5x 3000 F INSIDE

GYSCAP 12V DC/DC
1 600 A DC/DC converter

087651
1.7 m - 25 mm² Cables 100% Cu



24 V

10x 3000 F INSIDE

GYSCAP 24V DC/DC
2 500 A DC/DC converter

088504
2 m - 35 mm² Cables 100% Cu




GYSCAP 24V
2 500 A

028944
2 m - 50 mm² Cables 100% Cu


CHARGING MODES

On charged vehicle battery



12 V

max 2 min 30
max 9 min



24 V

max 4 min


GYSCAP 12V & TWIN START EV 12V DC/DC

GYSCAP 24V DC/DC

GYSCAP 24 V

DC/DC CONVERTER

On discharged vehicle battery



OPTION GYSFLASH for mains charge

4.12 + F5 p.6
029422 029439

12.12 + S7 p.7
029392 077331

max 15 min max 8 min

max 30 min max 16 min

max 1 h max 1 h




GYSCAP
TWIN START

★★★★★

The Complete & Safe solution

for combustion & EV engine

NEW 03/2026



12 V

5x 3000 F INSIDE

GYSCAP TWIN-START EV 12V DC/DC
1 600 A DC/DC converter TWIN

089990
Cables 100% Cu 1.7 m - 25 mm²




BREVET GYS
GYS PATENT



2IN1

+ 12 V Booster

+ Special EV Rescue



GYSCAP

BOOSTERS • SUPER CAPACITORS INSIDE

MADE IN FRANCE	START			START PETROL & DIESEL	EV/HEV	Number of Capacitors	DC/DC	INPUT CHARGE		cm	kg
	1 V/Cell	0 V/Cell	Peak								
GYSCAP 12V DC/DC	1 600 A	2 700 A	10 000 A	Pb/Lithium LFP	12 V	5 × 3000 F	•	8-16V / 50 A max	4,5V-30V / 8 A max	35 × 44 × 19	7,2
GYSCAP TWIN-START EV 12V DC/DC					14V/50A max						
GYSCAP 24V DC/DC	2 500 A	4 500 A	10 000 A	Pb/Lithium LFP	24 V	10 × 3000 F	•	16-32V / 50 A max	4.5V-30V / 8 A max	35 × 38 × 20	13
GYSCAP 24V							-	24V	10-30 V (150 W max)	32 × 49 × 21.5	14
Recommendation											
GYSCAP 12V DC/DC											
GYSCAP TWIN-START EV 12V DC/DC											
GYSCAP 24V DC/DC											
GYSCAP 24V											
225 Ah											
225 Ah											



ACCESSORIES

TRADITIONAL TESTERS	72
CONNECTED TESTERS	72
DIGITAL / COLOR SCREEN TESTERS	73
TESTERS WITH PRINTERS	74

POWER INVERTERS	76
PORTABLE ENERGY	78

ACCESSORIES	80
EV CHARGING	81
EV BATTERY ACCESSORIES	82
EV BATTERY LIFT / BATTERY LIFT	83
WORKING SUPPORTS	84
JUMPER CABLES	86
ACCESSORIES	87
WORKING LIGHTS	90

TBP

TRADITIONAL TESTERS



TBP 100
6/12 V 20 > 100 Ah
PB BATTERY
055131

TBP 500
12 V 10 > 160 Ah
PB BATTERY
055148

BTW

CONNECTED TESTERS



BTW 6V/12V
6/12 V 7 > 240 Ah
ALTERNATOR 12 V PB BATTERY
077355

BT

DIGITAL TESTERS



BT 001
12 V 7 > 230 Ah
PB BATTERY
056640



NBT 200
12 V 20 > 150 Ah
ALTERNATOR 12 V PB BATTERY
024168

DBT

COLOR SCREEN TESTERS




DBT 410
6/12 V 7 > 240 Ah
ALTERNATOR 6/12 V PB BATTERY
083233



DBT 500
6/12 V 7 > 240 Ah
ALTERNATOR 6/12 V PB BATTERY
079823



DBT 710
6/12 V 7 > 240 Ah
ALTERNATOR 6/12/24 V PB BATTERY
083585



MADE IN CHINA			TEST			DIGITAL	RESULT		TEMPERATURE COMPENSATION		kg		cm		L x W x H cm / kg
			BATTERY A	BATTERY V	CHARGE & START SYSTEM VEHICLE										
TBP 100	6-12V	20 > 100 Ah	•	•	12V	—	5/10s	—	—	1.5	16x1.8x30	30.7x17.2x10.3 / 1.5	15 min	—	—
TBP 500	12V	10 > 160 Ah	•	•	12V	—	15s	—	—	3.75	27x26x13	31x28.6x18.2 / 3.8	15 min	—	—
BTW 6V/12V	6-12V	7 > 240 Ah	—	min 4.5V	12 V	—	1s	•	•	0.11	11x3x2	7.5x4.5x16.4 / 0.16	instant	•	•
BT 001	12V	7 > 230 Ah	—	•	12 V	LED	1s	—	—	0.29	3x12x1.5	24.2x11.8x2.4 / 0.29	instant	•	•
NBT 200	12V	20 > 150 Ah	•	min 7V	12 V	•	1s	—	—	0.25	7x1.5x12	5x18x25.8 / 0.3	instant	•	•
DBT 410	6-12V	7 > 240 Ah	•	min 5V	6 / 12V	color screen 2.4"	1s	•	•	0.24	8x1.8x13.4	4.2x8.5x15	instant	•	•
DBT 500	6-12V	7 > 240 Ah	•	min 5V	6 / 12V	color screen 2.4"	1s	•	•	0.3	8x2x14	5x18.5x18.5 / 0.44	instant	•	•
DBT 710	6-12V	7 > 240 Ah	•	min 3 V	12 / 24V	color screen 3.2"	1s	•	•	0.9	10x3.5x20.5	10x18.4x25.3	instant	•	•

 Recommendation	TEST													CURRENT CCA SAE
	Battery/Batteries /Ladegeräte	Alternator Circuit/ Circuit alterateur/ Lichtmaschine/Schaltkreis		LIQUID	START /STOP ENGINE	EFB	AGM VRLA/GEL							
TBP 100			12 V	•	—	—	—			20 > 100 Ah				—
TBP 500		 	12 V	•	—	—	—			10 > 160 Ah				0 > 1000 A
BTW 6V/12V		 	12 V	•	•	•	•	7 > 240 Ah						10 > 2000 A
BT 001		 	12 V	•	•	•	•	7 > 230 Ah		7 > 230 Ah				—
NBT 200		 	12 V	•	—	—	•			20 > 150 Ah				200 > 1200 A
DBT 410		 	6-12 V	•	•	•	•	7 > 240 Ah						10 > 2000 A
DBT 500		 	6-12 V	•	•	•	•	7 > 240 Ah						100 > 2000 A
DBT 710		 	6-12-24 V	•	•	•	•	7 > 240 Ah						—





POWER INVERTERS

12/24 V DC > 230 V AC



PSW REMOTE CONTROL

For 601W-12



6 m




For 1002W RC-12, 1502W RC-12, 2002W RC-12, 2002W RC-24, 3000W RC-12, 000V RC-24



6 m


Input = 888 V
Output = 888 W

MSW / PSW TECHNOLOGY





- Under-voltage / Over-voltage / Overload / Overheating / Output short-circuit
- Tension faible / Surtension / Surcharge / Surchauffe / Court-circuit
- Unterspannung / Überspannung / Überlastung / Überhitzung / Kurzschluss am Ausgang

Power based on output voltage
Puissance en fonction de la tension de sortie
Leistung in Abhängigkeit von der Ausgangsspannung



Power based on temperature
Puissance en fonction de la température
Leistung in Abhängigkeit von der Temperatur



SELECT THE RIGHT POWER INVERTER

- CHOISISSEZ VOTRE CONVERTISSEUR
- WÄHLEN SIE IHREN WECHSELRICHTER

HOME APPLIANCE - ÉLECTROMÉNAGER				
 Microwave - Micro-Ondes - Mikrowelle		700 - 1000 W	30 - 50 min	1 h 30 - 2 h
 Toaster - Grille Pain		800 - 1500 W	20 - 40 min	1 h - 2 h
 Fridge - Réfrigérateur - Kühlschrank (40 L)		45 W	12 h	35 h
 Kettle - Bouilloire - Wasserkocher		700 - 2500 W	15 - 45 min	35 min - 2 h
 Espresso coffee maker - Cafetière espresso - Espresso-Maschine		1000 - 1600 W	20 - 30 min	1 h - 1 h 30
 Drip coffee maker - Cafetière filtre - Filterkaffee-Maschine		800 - 1200 W	25 - 40 min	1 h 30 - 2 h
ELECTRONIC - ÉLECTRONIQUE				
 Mobile phone - Téléphone - Telefon		5 - 10 W	55 - 110 h	155 - 310 h
 Laptop - Ordinateur portable		60 - 95 W	5 - 9 h	16 - 28 h
 Radio		10 - 40 W	14 - 55 h	40 - 155 h
 TV 15"		40 W	13 h 30	39 h
 TV 21"		50 W	11 h	31 h
 Video game console - Console de jeux vidéo - Konsole für Videospiele		39 - 100 W	5 - 13 h	16 - 39 h
 Camera - Appareil photo - Fotoapparat		4 - 19 W	25 - 135 h	78 - 390 h
COMFORT - CONFORT				
 Light - Eclairage - Beleuchtung		100 W	5 h 30	16 h
 Electrical heater - Chauffage électrique - Elektrische Heizung		1800 - 2500 W	12 - 20 min	35 - 45 min
 Fan - Ventilateur - Lüfter		50 W	11 h	31 h
 Hairdryer - Sèche cheveux - Fön		1000 - 2000 W	15 - 30 min	45 min - 1h 30
SAILING - NAUTISME				
 Navigation lights - Feux de navigation - Navigationslichter		24 W	30 h	80 h
 Radar		24 W	30 h	80 h
 Autopilot mode - Pilote automatique		60 W	9 h	30 h
 GPS/Sat nav. - GPS		6 W	110 h	310 h

* Usage duration (h) = $\frac{80\% \times \text{Capacity (Ah)} \times \text{Optimum Efficiency (\%)} \times \text{Input DC (V)}}{\text{Power (W)}}$

MADE IN CHINA	Power	Peak power	Pure Sin Wave	Optimum Efficiency	Input DC	Output AC	Output USB (2.1) DC	max 150W	cables	1.5 mm ²	2.5 mm ²	Universal	key	remote	weight	cm	L x W x H cm / kg
CONVERGYS 150	150W	300W	—	90,5%	12V	230V	5V · 2A	•	—	•	•	•	—	—	0,5 kg	N/A	8 × 16,5 × 24,7 / 0,45
CONVERGYS 300	300W	600W	—	85%	12V	230V	5V · 2A	•	•	•	•	•	—	—	0,95 kg	N/A	21,3 × 20 × 6,8 / 0,95
PSW 601W RC-12	600W	1200W	•	90%	12V	230V	5V · 2A	—	cables	6 mm ²	•	•	•	6 m	2,2 kg	26,5 × 17 × 7,5	31 × 22 × 12 / 2,3
PSW 1002W RC-12	1000W	2000W	•	90%	12V	230V	5V · 2A	—	cables	10 mm ²	•	•	•	6 m	4,7 kg	37,5 × 21 × 10	44 × 27 × 16 / 4,5
PSW 1502W RC-12	1500W	3000W	•	90%	12V	230V	5V · 2A	—	cables	16 mm ²	•	•	•	6 m	5 kg	37,5 × 21 × 10	44 × 27 × 16 / 4,6
PSW 2002W RC-12	2000W	4000W	•	90%	12V	230V	5V · 2A	—	cables	22 mm ²	•	•	•	6 m	6,25 kg	38,5 × 25 × 10	43 × 32 × 16,5 / 5,7
PSW 3000W RC-12	3000W	6000W	•	85%	12V	230V	5V · 2A USB-C 18 W (5V/3.1A - 9V/2A - 12V/1.5A)	—	cables	18 mm ²	•	•	•	6 m	10,7	49,8 × 28,8 × 14,2	58 × 35 × 28 / 11,2
MSW 82000	2000W	4000W	—	80%	24V	230V	5V · 2A	—	cables	12 mm ²	•	•	•	—	5,8 kg	35 × 20 × 28	45,3 × 26,8 × 16,1 / 4,9
PSW 2002W RC-24	2000W	4000W	•	90%	24V	230V	5V · 2A	—	cables	12 mm ²	•	•	•	6 m	6,25 kg	38,5 × 25 × 10	43 × 32 × 16,5 / 5,7
PSW 3000W RC-24	3000W	6000W	•	85%	24V	230V	5V · 2A USB-C 18 W (5V/3.1A - 9V/2A - 12V/1.5A)	—	cables	18 mm ²	•	•	•	6 m	10,7	49,8 × 28,8 × 14,2	58 × 35 × 28 / 11,2

12 V



CONVERGYS


CONVERGYS 150
027022



CONVERGYS 300
027053
027046



12 V



PURE SINE WAVE

PSW
601W RC-12

067332
067349



PSW
1002W RC-12

067356
067363



PSW
1502W RC-12

067370
067387



PSW
2002W RC-12

067394
067400




PSW
3000W RC-12

089853



NEW
01/2026


24 V



MODIFIED SINE WAVE

MSW 82000

027237
027244



PSW
2002W RC-24

067417
067424



PSW
3000 RC-24

089860



NEW
01/2026


INCLUDED
FOR ALL



48 cm



48 cm



1 m



POWER PACK

PORTABLE ENERGY


DC/AC - Li inside

OPTIONS

Solar panel

for Power pack 520, 14.22, Energys DC/DC
monocrystalline
ETFE quality - 18V - 100 W max

OUTPUT
USB 1 : 5V/3A
USB 2 : 5V/3A ; 9V/2A ; 12V/1.5A
Type C : 5V/3A ; 9V/2A ; 12V/1.5A
Jack : 18V/5.6A max
079410



5 MODES
Light (Low, Medium, High) / S.O.S. / Flash



3 MODES
Light / S.O.S. / Flash



POWER PACK 520

518 Wh

500 W

027961



POWER PACK 14.22

1408 Wh

2200 W

085206



USAGE DURATION

	50 W	100 W	250 W	500 W	1000 W	1500 W	2200 W
POWER PACK 520	8 h	4 h	1 h 40	50 min	—	—	—
POWER PACK 14.22	22 h	11 h	4 h 30	2 h 15	1 h 05	45 min	30 min
POWER PACK 14.15 FC	22 h	11 h	4 h 30	2 h 15	1 h 05	45 min	—

FULL PROTECTION

Short-circuit protection,
Over-current protection,
Over-voltage protection,
Under-voltage protection
Over-load protection,
Temperature protection

MPPT
integrated

Solar panel
compatibility

OPTIONS

Power batt 14 External battery

for Power pack 14.15 FC
085213


1408 Wh - LiFePO4
42 x 30 x 25.5 cm / 12.8 kg



Solar panel

for Power pack 14.15 FC
079403

monocrystalline - ETFE quality
48V - 220 W max
OUTPUT : MC4



POWER PACK 14.15 FC

1408 Wh

1500 W

085169



	LITHIUM Battery		INPUT	RECHARGING TIME			AC OUTPUT			DC OUTPUT	LIGHT	BOOSTER			OPTION COMPATIBILITY		L x W x H cm / kg	L x W x H cm / kg
	CAPACITY	TYPE		MAINS 0-100 %	SOLAR PANEL 0-100 % (depending on weather conditions)	DC CHARGING 0-100 %	230 V / 50 Hz (Pure Sine Wave)	Rating POWER OUT	Peak Power OUT			12V Petrol & Diesel (Lead / LFP)	1V/Cell	0V/Cell	SOLAR PANEL	EXTERNAL BATTERY		
POWER PACK 520	20 Ah 518 Wh	LiPo	JACK DC ø3.5 (Main / solar charging): 12-30V 80W PD USB-C (DC charging): 45W	6 h 30	8 h 30 - 11 h 30	11 h 30	(x2) Type C / E / F / G / I	500 W	750 W (3sec)	(x1) PD USB-C : 45W max (x1) QC USB-C : 18W max (x2) USB-A : 5V - 2.4A	(x1) LED	—	—	—	•	—	26.4 x 23.4 x 16.3 / 5.14	33.5 x 23 x 34.5 / 6.2
POWER PACK 14.22	55 Ah 1408 Wh	LFP	JACK DC ø5.5 (Main / solar charging): 12-30V 200W	7 h 30	13 h - 15 h	—	(x3) Type C / E / F (euro plug)	2200 W	4400 W	(x3) USB-A : 5V - 2.4A (x1) QC USB-A : 18W max (x2) PD USB-C : 100W max	(x1) LED	•	500 A	1000 A	•	—	36 x 27 x 28 / 17.1	—
POWER PACK 14.15 FC	55 Ah 1408 Wh	LFP	C14 EURO PLUG (AC charging): 230Vac 1500W ANDERSON (solar charging): 30-60V 400W JACK DC ø5.5 (DC charging): 12V 120W	1 h	6 h - 8 h	11 h	(x3) Type C / E / F (euro plug)	1500 W	3000 W	(x3) USB-A : 5V - 2.4A (x1) QC USB-A : 18W max (x2) PD USB-C : 100W max	(x1) LED	•	500 A	1000 A	•	•	36 x 27 x 28 / 19.3	43 x 36.5 x 33.5 / 22

RECOMMENDATION	Game	Phone	Tools	Laptop	TV	Tablet	Drill	Saw	Hammer	Wrench	Router	Planer	Sander	Grinder	Polisher	Blower	Generator
POWER PACK 520	•	•	•	•	•	•											
POWER PACK 14.22	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
POWER PACK 14.15 FC	•	•	•	•	•	•	•	•	•	•	•						

AIR COMPRESSOR

NOMAD AIR
COMPRESSOR
088795

NEW



- 5 INFLATION MODES
- Car (2.50 bars)
 - Motorbike (2.40 bars)
 - Ball (4.10 bars)
 - Bike (0.55 bars)
 - Favorites (1.40 bars)
- Ultra light & Compact


	LITHIUM Battery							
	CAPACITY	TYPE	FULL CHARGE					
NOMAD AIR COMPRESSOR	2.5 Ah / 27.75 Wh	Lico02	2h15	10 bars	USB-C: 5V/2A	(x1) USB-A: 5V - 2.1A	6.4 × 5.65 × 17.55 cm	0.61 kg

MEMORY SAVER

NOMAD OBD
MEMORY SAVER
085480



INSIDE	MEMORY SAVER			
	OBD < 4 A	< 4 A		
Li-ion 12V - 2 Ah			14.5 × 7.2 × 3.5 cm	515 g



Connected to booster

CABLE OBD
- Câble OBD
- Kabel für OBD



MEMORY AUTO SAVE CABLE OBD
Fuse 7,5 A - 1,5 m
054202

EV CHARGING

Rechargement EV • Laden für Elektrofahrzeuge
• Carga de EV • Ricarica per veicoli elettrici

6 A > 32 A

Power Grid		RECHARGE TIME (20 to 100%)*															
		230 V (1 ph)								400 V (3 ph)							
		6 A 1.4kW	8 A 1.8kW	10 A 2.3kW	13 A 2.9kW	16 A 3.7kW	20 A 4.6kW	32 A 7.4kW	6 A 4.1kW	8 A 5.5kW	10 A 6.9kW	13 A 8.9kW	16 A 11kW	20 A 14kW	32 A 22kW		
Example of battery capacity	10 kW	6 h	4 h30	3 h30	3 h	2 h	1 h30	1 h	2 h	1 h30	1 h	50 min	40 min	-	-		
	20 kW	12 h	9 h	7 h	5 h30	4 h30	3 h30	2 h	4 h	3 h	2 h30	2 h	1 h30	-	-		
	50 kW	29 h	22 h	18 h	13 h	11 h	9 h	5 h30	9 h	7 h30	6 h	4 h30	3 h	2 h30	1 h30		
	60 kW	35 h	26 h	21 h	16 h	13 h	10 h30	6 h30	11 h30	9 h	7 h	5 h30	4 h	3 h30	2 h		
	70 kW	40 h	30 h	24 h	19 h	15 h	12 h	7 h30	13 h30	10 h	8 h	6 h30	5 h	4 h	2 h30		
	80 kW	46 h	34 h	27 h	22 h	17 h	14 h	8 h30	15 h30	11 h30	9 h	7 h	6 h	4 h30	3 h		

*Indicated values

INCLUDED		075320	080676
		✓	—
16 A / 1 ph		✓	—
13 A / 1 ph		—	✓
32 A / 3 ph		✓	✓
16 A / 1 ph		—	✓

+ more input options...

available on request

IP 65

↓ 23 × 16 × 9 cm
↑ 46 × 20.5 × 38 cm / 6 kg



SUPER PRO SMART
EV CHARGE

6 → 32A 1ph / 3ph

TIMER FUNCTION
Delay start 1h → 24h

075320
080676



EV CHARGING - PORTABLE
10/16 A 1 ph
028975



EV CHARGING - STANDARD CABLES
32 A 1 ph
079687



EV CHARGING - SPIRAL CABLE
32 A 1 ph
028982

	IP	U ₁	I ₁	P				
SUPER PRO SMART EV CHARGE	65	1 ph 3 ph + N	6/8/10/13/16/20/32 A	1,4 → 22kW	•	—	5 m	Type 2
EV CHARGING PORTABLE	66	1 ph	10 / 16 A	2,3 / 3,7kW	•	—		Type 2
EV CHARGING SPIRAL CABLE	66	1 ph	32 A	7,4 kW	—	•		Type 2
EV CHARGING STANDARD CABLES	55	1 ph	32 A	7,4 kW	—	•		Type 2
	55	3 ph	32 A	22 kW	—	•		



OPTION
↓ 21 × 43 × 57 cm
060432

EV BATTERY ACCESSORIES

EQUIPMENT FOR EV AND HYBRID APPLICATIONS - Équipements pour opérations sur véhicules électriques & hybrides - Ausrüstung für den Betrieb von Elektro- und Hybridfahrzeugen

FACE SHIELD WITH HEADBAND
- ÉCRAN FACIAL AVEC SERRE-TÊTE
068018



INSULATING GLOVES (T10)
- GANTS ISOLANTS (T10)
068025



JACKET - Veste - Jacke



98% cotton,
2% antistatic
EN ISO 11612
A1+A2-B1-
C1-E3-F1
S (40/42)
046368
M (44/46)
046375
L (48/50)
046382
XL (52/54)
046399
XXL (56/58)
046412
IEC 61482-2
Class 1-4kA
EN 1149-5
EN ISO 11611
Class 2-A1
& A2
EN 14404
+A1
Type 2

TROUSERS - Pantalon - Hose



98% cotton,
2% antistatic
EN ISO 11612
A1+A2-B1-C1-E3-F1
S (40/42)
046313
M (44/46)
046320
L (48/50)
046337
XL (52/54)
046344
XXL (56/58)
046351
EN ISO 11611
Class 2-A1 & A2
IEC 61482-2
Class 1-4kA
EN 14404
+A1
Type 2
EN 1149-5

Working zone warning kit
- Kit pour le balisage de la zone d'intervention
- Kennzeichnungsset für Hochvolt-Bereiche
064409

Red and white warning pole - Balise de signalisation rouge et blanche	x 4
Red and white bounding line - Chaîne de délimitation rouge et blanche	x 1
Sign board "Danger, working area EHV" - Pancarte de signalisation "Danger, zone de travail VEH"	x 2



EV BATTERY LIFT

1T MOBILE LIFTING TABLE WITH HYDROPNEUMATIC PUMP - Table élévatrice mobile 1 tonne avec pompe hydropneumatique - Mobiler 1-Tonnen-Hubtisch mit hydropneumatischer Pumpe

083912
Weight : 385 kg

max : 148 cm
min : 130 cm

1 t
max



Hydropneumatic pump
- Pompe hydropneumatique



110 s
30 s

1.2T LIFTING TABLE FOR ELECTRIC VEHICLE BATTERIES - Table de levage 1.2T pour batteries de véhicule électrique - 1,2T Hubtisch für Elektrofahrzeugbatterien

083929
Weight : 760 kg

max : 207 cm
min : 174 cm

1.2 t
max



BATTERY LIFT

JOBSITE XL HAND TROLLEY
039568


18.3 kg 66 x 47 x 20 cm / 19.5 kg



MULTITOOL TRUCK
max 200 kg

067158
90 kg
123 x 79 x 39 cm / 95 kg

INCLUDED



SAFE
EN 14238 + A1



BATTERY LIFT
ACCESSORIES

WORKSHOP EQUIPMENT

ROUND STOOL WITH TOOL STORAGE

- Tabouret - Werkstatt-Rollhocker

057555
38 x 38 x 44 cm - 5.2 kg
⊗ 41 x 19 x 41 cm / 5.6 kg



PLASTIC STOOL WITH TOOL STORAGE

- Tabouret en plastique avec rangements - Kunststoffhocker

085916
3.9 kg
⊗ 61 x 36 x 16 cm / 4.6 kg



3-DRAWER WORKSHOP STOOL

- Tabouret d'atelier 3 tiroirs - Werkstattthocker 3 Schubladen

079878
47 x 35 x 43 cm / 12 kg
⊗ 38.5 x 37 x 38.5 cm / 13 kg



FOLDING STEP STOOLS - Marche pieds (Aluminium)


- Arbeitspodest klappbar

080041
7.3 kg
⊗ 100 x 39.5 x 19 cm / 8.1 kg




057562

7.9 kg
⊗ 102 x 39 x 19 cm / 8.5 kg



058552

⌵ 113 x 41 x 16 cm / 16 kg
⊗ 117 x 42 x 17 cm / 17 kg



MECHANICS CREEPER WITH TILTING HEADREST

- Chariot de visite - Werkstatt-Rollliege

057548
102 x 43 x 11 cm / 5.3 kg
⊗ 104 x 45 x 13 cm / 6 kg



2 IN 1 MECHANICS CREEPER

- Chariot de visite 2 en 1 - Werkstatt-Rollliege


079861
102 x 40 x 14 cm
⊗ 40 x 13 x 63 cm - 7.6 kg



WORKSTATION PREMIUM 5 DRAWERS

- Servante premium 5 tiroirs

076143
⌘ 64 kg
Capacity 320 kg



PLASTIC TROLLEY 3 SHELVES

- Servante plastique 3 plateaux



WORKSTATION 3 SHELVES 1 DRAWER

- Servante d'atelier 3 plateaux 1 tiroir



ACCESSORIES

MANUAL TOOL FOR BLIND RIVETS

For BLIND rivets - Pour rivets POP - Für Blindniet

Steel / Acier Ø 3.2/4.0/4.8/6./6.4
Alu Ø 3.2/4.0/4.8/6./6.4

061323

Made in Taiwan

MAGNETIC COVER - Couverture magnétique - Magnetschutzdecke

1.06 m x 0.6 m
061446

INFRARED THERMOMETER

Adjustable emissivity: 0.10 ~ 1.00

079922

-50 / +600 °C
-58 / +1112 °F

GLOVES - Gants - Handschuhe - Guantes

Anti-cut - Anti coupure T9 045897

✓ touch screen friendly - écran tactile

High resistance anti-cut - Anti coupure haute résistance EN 420 EN 388:4121 T9: 045910 T10: 045927

High dexterity anti-cut - Anti coupure haute dextérité EN 420 EN 388:1121 T9: 045903 T10: 045934

Cult. Leather Leder

Ultra Flexible

T10 064188

EN388 4342C

EN388 2011 X

EN420 2003 +A1

HEAT COVER - Couverture anti-chaleur - Hitzeschutzdecke - Manta anti-calor - Protecção anti-aquecimento

PROTEC 550 550°C/1000°F - Class M0 2 m x 2 m - 580 g/m² 050495

PROTEC 1200 1200°C/2200°F - Class M0 1.75 m x 1.5 m - 1200 g/m² 050204

PROTEC 1300 1300°C/2400°F - Class M0 XL: 2 m x 1.8 m 620 g/m² 053595

PROTEC 1300L 1300°C/2400°F XL: 2 m x 1.8 m 420 g/m² 060500

RESPIRATORY MASKS - Masques respiratoires - Atemschutzmaske - Máscaras respiratorias

FFP3 - EN 140 / EN 143 / EN 166 (x1) Size M/L 037021

FFP3 - EN 140 / EN 143 (x1) Size M/L 037014

Étui / Case 037045

FFP3 - EN 143 : 2000 P3 Anti poussières / Anti odeurs 037038

PROTECTION GOGGLES

EN 166

Shade/IR0 042810

Shade/IR0 042827

Shade/IR5 042841

Shade/IR0 047778

Shade/IR0 047792

SET OF 2 MAGNETS

(x2) 052291

JUMPER CABLES

320 A > 1000 A

056206									
564015									
056404									
056602									
056190									
056312									
056329									
056336									
056343									
056558									
056541									
056619									

PRO BRASS CLAMPS

BRASS CLAMPS, NON-INSULATED - Pincles laiton, non isolées - Messingklemmen, nicht isoliert - Pinzas de latón, no aisladas - Morsetti in ottone non isolati



056206	320 A	3 m	—	16 mm²	(CCA)				
564015	500 A	3 m	—	25 mm²	(CCA)				
056404	700 A	4,5 m	—	35 mm²	(CCA)				
056602	1000 A	5,1 m	—	50 mm²	(100% Cu)				
056190	1000 A	4,5 m	INCLUDED	50 mm²	(100% Cu)				

PRO INSULATED CLAMPS

INSULATED CLAMPS - Pincles isolées - Isolierte klemmen - Pinzas aisladas - Morsetti isolate



		ESSENCE BENZINE PETROL	DIESEL							
056312	200 A	1,5l		3 m	—	10 mm²	≈ Ø Cu	—		
056329	320 A	2,5l		3 m	—	16 mm²	≈ Ø Cu	•		
056336	500 A	5,5l	3l	3,5 m	—	25 mm²	≈ Ø Cu	•		
056343	700 A	7l	4l	4,5 m	—	35 mm²	≈ Ø Cu	•		
056558	1000 A	7l	4l	4,5 m	INCLUDED	50 mm²	(100% Cu)	—		

SUPER PRO INSULATED CLAMPS

INCLUDED

ANTI-ARC PROTECTION x2

MADE IN FRANCE

056541	700 A	4,5 m	35 mm²	100% Cu					
056619	1000 A	5 m	50 mm²	100% Cu					

INSPECTION LAMP - Lampe inspection - Inspektionslampen


FRONTAL INSPECTION LAMP 280 L

100-280 lumens

3 W COB LED
80 CRI+, 6500 K
3.7 V - 1500 mAh Li-po
micro USB charging
operating time
High position : 2 h
Low position : 6 h

IP 65 / 23 x 7.8 x 4.7 x 4.2 cm
40 x 8.8 x 5.5 cm / 200 g

060845



HANDS-FREE TORCH 360 L

180-360 lumens

3.7 V - 2200 mAh Li-ion
Charging time: 3.5 h
operating time
High position : 3 h
Low position : 6 h

26 x 15.9 x 2.5 cm
3.5 x 30 x 16 cm

088559

NEW



PORTABLE LAMP 400 L

400 lumens

COB LED
Li-ion
Charging time : 8 h
operating time
High position : 2.5 h
Low position : 5 h
Top light (1 W) : 6 h

23 x 6.5 x 4 cm / 480 g
13 x 7 x 23.5 cm

059153



INSPECTION LAMP MINI 350 L

0-350 lumens

COB LED
3.7 V - 1100 mAh Li-ion
USB charging (3 h)
operating time
3 > 6.5 h

IP 20

075894

50 lumens

120 lumens

350 lumens



INSPECTION LAMP PRO 800 L

120-800 lumens

COB LED
3.7 V - 2600 mAh Li-ion
USB charging (4 h)
operating time
2.5 > 9 h


IP 54

075900

120 lumens

120 / 400 lumens

150 / 800 lumens



UNDER BONNET LAMP - Lampe sous capot - Leuchte für Motorhaube

UNDER BONNET LAMP 600 L

500-1000 lumens

120 COB LED
3.7V - 4000 mAh Li-ion
charging time : 10/12 h
operating time
High position : 4 h
Low position : 8 h

26 x 10 x 10 cm
2.3 kg
23.5 x 12 x 69.5 cm

059962



UNDER BONNET LAMP 800 L

250-800 lumens

120 COB LED
3.7V - 4000 mAh Li-ion
charging time : 10/12 h
operating time
High position : 3 h
Low position : 6 h

2 kg
60.7 x 15 x 11.3 cm

058002



WORKLIGHT WITH TRIPOD - Projecteur sur trépied - Arbeitsleuchte mit Standfuß

TRIPOD LAMP 3000 L

3000 lumens

35 W COB LED
2 m power cord

IP 44
4.1 kg
103 x 21.5 x 10 cm

059979




TRIPOD LAMP 4000 L

4000 lumens

3 x 20 COB LED,
total 60 LED
3 m power cord

6.4 kg
22 x 16 x 116 cm

059986



AUTOMOTIVE BATTERIES

Batteries de démarrage - Starterbatterien - Baterías de arranque
- Automotive accu's - Baterias de Automóvel - Minotrapiec
огудитив - Пусковые батареи - 汽车启动电池

Curves	Pb* (except gel)	Pb* (incl. gel)	Battery overcharged protection	100% charged	Maintenance	Battery desulphation	Fast Charge	Fast Charge ++
W	✓	-	-	✓	-	-	-	-
W2	✓	-	✓	-	-	-	-	-
WU	✓	-	✓	-	✓	-	-	-
WUoU	✓	✓	✓	✓	✓	-	-	-
IWUoU	✓	✓	✓	✓	✓	✓	✓	-
I REGULATED IUoU FAST CHARGE	✓	✓	✓	✓	✓	(except Artic)	✓	✓
7 STEP GYSFLASH Pb	✓	✓	✓	✓	✓	✓	✓	✓

* Pb : AGM / EFB / VRLA / Liquid / SLI / SLA / Calcium...

GYSFLASH Lithium


8 STEP
Li-ion

8 STEP
LiFePO₄


9 STEP
Li-ion

9 STEP
LiFePO₄



LiFePO₄ / Li-ion / Li-Po / NMC /
LCO / MCO / NCA...



Parallel




Serial



MARKETING



Catalogs and posters available
for download on our website
www.gys.fr



A - Marquee
3 x 3 m
098022

B - Open
Marquee
2 x 2 m
098039

C - Banner
3 x 0.50 m
098015



Display stand - Podium de
présentation - Podest
(machines not included)

063204
A : 45 cm, B : 50 cm, C : 50 cm
063211
A : 80 cm, B : 50 cm, C : 50 cm



Retail display space with 2 shelves
- Linéaire de vente avec 2 étagères
- Lochwandregal mit 2 Böden
(machines not included)
060784



Type	FA1	FA2	SB1
complete - complet - komplett	062429	062443	061149
without display stand - sans linéaire - ohne Regal	062436	062450	062412



INVEST IN THE FUTURE

CHARGE

2026

GYS France

Headquarters

1 rue de la Croix des Landes
CS 54159
53941 Saint-Berthevin - Cedex
Laval - France
Tel +33 2 43 01 23 60
E-mail service.client@gys.fr



ZI, 134 bd des Loges
53941 Saint-Berthevin
Laval - France

Logistics center

2 Rue Jean Dausset
53810 Changé - France
Tel +33 2 43 01 54 33

GYS Germany

Professor-Wieler
Straße 11
52070 Aachen
Deutschland
Tel +49 241/189-23-710
Fax +49 241/189-23-719
E-mail aachen@gys.fr

GYS UK

Unit 3 - Great Central Way
Rugby - Warwickshire
CV21 3XH
United Kingdom
Tel +44 1926 338 609
Fax +44 1926 429 764
E-mail uk@gys.fr

GYS Italia

Via Porta Est, 7
30020 Marcon - VE
Italia
Tel +39 041 53 21 565
E-mail italia@gys.fr

GYS Ibérica

Avenida Pirineos 31
Nave 9
San Sebastian de los Reyes
28703 Madrid
España
Tel +34 917 409 790
E-mail iberica@gys.fr

GYS China

Lot N°15 - 6666 bd Songze
201706 Qingpu
Shanghai - China
Tel +86 6221 4461
Fax +86 5226 0067
www.gys-china.com.cn
E-mail
contact@gys-china.com.cn

LinkedIn
 Youtube
 WeChat
 Facebook
 Instagram



www.gys.fr



Distributed by